



CLIMAFLEX® SYSTEM

Fittings and valves can develop into weak spots if they are not properly insulated. This can lead to the risk of energy losses and defrost water. CLIMAFLEX® SYSTEM is designed to put a stop to such risks, and also complies with the German energy saving ordinance. The universal insulation cap with versions for Y-type, ball and circulation valves can be used with components from various manufacturers in the common values (DN 15 to DN 50). The seals are designed to be reusable and are easy to fit. Cutting is simple, using just a cutter or die.

Product features

- Thermal conductivity (EN ISO 8497):
0,037 W/mK at 0°C
0,043 W/mK at 40°C
0,046 W/mK at 90°C
- Fire performance (EN 13501-1): Euroclasse E
- Temperature range: 0°C to 100°C (EN 14707)
- Thickness: DN 15, 20, 25, 32, 40, 50
- See website for Declaration of performance

www.nmc-insulation.com

NMC sa
Gert-Noël-Strasse B-4731 Eynatten Belgium
Phone: +32 87 85 85 00
Fax: +32 87 85 83 55
E-Mail: info@nmc.eu





Product range

CLIMAFLEX® SYSTEM SSV

Type	Reference	Packaging unit pcs
SSV	DN 15	20
SSV	DN 20	20
SSV	DN 25	15
SSV	DN 32	10
SSV	DN 40	5
SSV	DN 50	4

CLIMAFLEX® SYSTEM KHV

Type	Reference	Packaging unit pcs
KHV	DN 15	15
KHV	DN 20	10
KHV	DN 25	10
KHV	DN 32	9
KHV	DN 40	12

CLIMAFLEX® SYSTEM ZV

Type	Reference	Packaging unit pcs
ZV	DN 15	10
ZV	DN 20	9
ZV	DN 25	5