

DECLARATION OF PERFORMANCE

Product name : **EXZENTROFLEX® Compact**

DoP Nr. : W1PEF400

1. Unique identification code of the product-type:

	Unique identification code of the product-type:	W1PEF-004a	W1PEF-004b		
	Thickness :	Inner diameter:	Inner diameter:		
	9 mm	15-35 mm	-		
	25-51 mm	-	15-42 mm		

2. Intended use or uses:

Thermal Insulation for Building Equipment and Industrial Installations (ThIBell)

3. Manufacturer:

NMC sa, Gert-Noël-Straße, B-4731 Eynatten

5. System or systems of assessment and verification of constancy of performance:

System 3

6a. Harmonized standard:

EN 14313:2009+A1:2013

6b. Notified bodies:

NB 1004 IBP / NB 0761 IBMB

7. Declared performance(s):

	Unique identification code of the product-type:	W1PEF-004a	W1PEF-004b		
Requirement / Characteristics from the mandate	Requirement clauses in the european Standard	Performances : levels or classes	Performances : levels or classes		
Reaction to fire Euroclass characteristics	4.2.4 Reaction to fire	EI	EI		
Acoustic absorption index	4.3.7 Structure-borne sound transmission	NPD	NPD		
	4.3.8 Sound absorption	NPD	NPD		
Thermal resistance	4.2.1 Thermal conductivity	0,036 at 0°C	0,037 at 0°C		
		0,040 at 40°C	0,042 at 40°C		
		0,053 at 90°C	0,055 at 90°C		
	4.2.2. Dimensions and tolerances	See table 1 & 2 point 4.2.2.2. of the standard	See table 1 & 2 point 4.2.2.2. of the standard		
Water permeability	4.3.4. Water absorption	WS005	WS005		
Water vapour permeability	4.3.4 Water absorption	WS005	WS005		
	4.3.5 Water vapour diffusion resistance	NPD	NPD		
Compressive strength		a	a		
Rate of release of corrosive substances	4.3.6. Trace quantities of water soluble ions & pH-value	NPD	NPD		
Release of dangerous substances to the indoor environment	4.3.9. Release of dangerous substances	b	b		
Continuous glowing combustion	4.3.10 Continuous glowing combustion	b	b		
Durability of reaction to fire against ageing/degradation	4.2.5. Durability characteristics	c	c		
Durability of thermal resistance against ageing/degradation	4.2.1. Thermal conductivity	d	d		
		4.2.2. Dimensions and Tolerances	See table 1 & 2 point 4.2.2.2. of the standard	See table 1 & 2 point 4.2.2.2. of the standard	

	4.2.3. Dimensional stability	See 4.3.2	See 4.3.2		
	4.2.5. Durability characteristics	d	d		
	4.3.2. Maximum service temperature	ST (+) 100°C	ST (+) 100°C		
	4.3.3. Minimum service temperature	ST (-) 0°C	ST (-) 0°C		
Durability of reaction to fire against high temperature	4.2.5. Durability characteristics	c	c		
Durability of thermal resistance against high temperature	4.2.5. Durability characteristics	d	d		
	4.3.2. Maximum service temperature - dimensional stability	ST (+) 100°C	ST (+) 100°C		

Note:

NPD: No Performance Determined

a: Compressive strength is not applicable for PEF products

b: At the time of edition of this product standard, no CE test standard is available

c: The fire performance of polyethylene foam does not change with time

d: The thermal conductivity of polyethylene foam does not change with time

The performances of the product identified above is in conformity with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer.

Digital version of the Declaration of Performance is available on the website www.nmc-insulation.com/download.

Signed for and on behalf of the manufacturer by:

X. FISCHER
Quality Manager



Eynatten, 16-04-20

Gert-Noël-Straße, B - 4731 Eynatten