



CLIMAFLEX®

roll

MATERIAL

CLIMAFLEX® ROLL is a flexible insulating material made of closed-cell, cross-linked polyethylene foam.

THERMAL CONDUCTIVITY (EN 12667)

0,039 W/mK at 0 °C
0,045 W/mK at 40 °C
0,051 W/mK at 90 °C

TEMPERATURE RANGE (EN 14707)

0 °C to +100 °C

FIRE PERFORMANCE (EN 13501-1)

Euroclass E

APPLICATION AREA

Heating and plumbing

ADVANTAGES

- Cut as needed
- Professional thermal insulation for energy savings of up to 80 %
- Improvement of the economic and ecological efficiency of the entire unit
- Sound absorbing insulation for acoustic comfort

See website for Declaration of performance: www.nmc-insulation.com



NMC (UK) LTD.

Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277

Email: enquiries@nmc-uk.com


www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX®

roll



Type	A mm	B mm	Length m	Pkg unit m ²
1000 x 10	1000	10	30	30
1000 x 15	1000	15	25	25
1000 x 20	1000	20	25	25