

# DECLARATION OF PERFORMANCE

**DoP No:** W4FEF901 Insul Roll Cover Silver

1. **Unique identification code of the product-type:**  
W4FEF009
2. **Intended use or uses:**  
Thermal Insulation for Building Equipment and Industrial Installations (ThIBEII)
3. **Manufacturer:**  
Nmc Polska Sp. z o. o., 41-807 Zabrze, ul. Pyskowicka 15
4. **System or systems of assessment and verification of constancy of performance:**  
3
5. **Harmonized standard :**  
EN 14304:2009+A1:2013  
  
**Notified bodies:**  
NB 1454, NB, NB 1488, NB 0751
6. **Declared performance(s):**

Requirement / Characteristics from the mandate	Requirement clauses in the European Standard	Performances : levels or classes												
Reaction to fire Euroclass characteristics	4.2.4 Reaction to fire	D-s3,d0												
Acoustic absorption index	4.3.7 Structure-borne sound transmission	NPD												
	4.3.8 Sound absorption	NPD												
Thermal resistance	4.2.1 Thermal conductivity	0,034 at -30°C 0,036 at 0°C 0,039 at 40°C 0,044 at 70°C												
	4.2.2. Dimensions and tolerances	<table border="1"> <thead> <tr> <th>Wall thickness [mm]:</th> <th>Lenght:</th> <th>Width:</th> </tr> </thead> <tbody> <tr> <td><math>d_b \leq 6</math></td> <td><math>\pm 1,0</math></td> <td>- 1,5% + 5% <math>\pm 2\%</math></td> </tr> <tr> <td><math>6 &lt; d_b \leq 19</math></td> <td><math>\pm 1,5</math></td> <td></td> </tr> <tr> <td><math>d_b &gt; 19</math></td> <td><math>\pm 2,0</math></td> <td></td> </tr> </tbody> </table>	Wall thickness [mm]:	Lenght:	Width:	$d_b \leq 6$	$\pm 1,0$	- 1,5% + 5% $\pm 2\%$	$6 < d_b \leq 19$	$\pm 1,5$		$d_b > 19$	$\pm 2,0$	
Wall thickness [mm]:	Lenght:	Width:												
$d_b \leq 6$	$\pm 1,0$	- 1,5% + 5% $\pm 2\%$												
$6 < d_b \leq 19$	$\pm 1,5$													
$d_b > 19$	$\pm 2,0$													
Water permeability	4.3.4. Water absorption	WS 01												
Water vapour permeability	4.3.4 Water absorption	WS 01												
	4.3.5 Water vapour diffusion resistance	<table border="1"> <tbody> <tr> <td><math>d_b = 6-25 \text{ mm}</math> <math>\geq 10 \text{ 000}</math></td> <td><math>d_b = 32 \text{ mm}</math> <math>\geq 7000</math></td> </tr> </tbody> </table>	$d_b = 6-25 \text{ mm}$ $\geq 10 \text{ 000}$	$d_b = 32 \text{ mm}$ $\geq 7000$										
$d_b = 6-25 \text{ mm}$ $\geq 10 \text{ 000}$	$d_b = 32 \text{ mm}$ $\geq 7000$													
Rate of release of corrosive substances	4.3.6. Trace quantities of water soluble ions & pH-value	NPD												
Release of dangerous substances to the indoor environment	4.3.9. Release of dangerous substances	NPD												

Requirement / Characteristics from the mandate	Requirement clauses in the European Standard	Performances : levels or classes
Continuous glowing combustion	4.3.10 Continuous glowing combustion	NPD
Durability of reaction to fire against ageing/degradation	4.2.5. Durability characteristics	The product meets the requirements for this property, the characteristics does not change with time.
Durability of thermal resistance against ageing/degradation	4.2.1. Thermal conductivity	The product meets the requirements for this property, the characteristics does not change with time.
	4.2.2. Dimensions and Tolerances	As above
	4.2.3. Dimensional stability	ST (+) 105°C
	4.2.5. Durability characteristics	The product meets the requirements for this property, the characteristics does not change with time.
	4.3.2. Maximum service temperature	ST (+) 105°C
	4.3.3. Minimum service temperature	ST (-) 50°C
Durability of reaction to fire against high temperature	4.2.5. Durability characteristics	The product meets the requirements for this property, the characteristics does not change with time.
Durability of thermal resistance against high temperature	4.2.5. Durability characteristics	The product meets the requirements for this property, the characteristics does not change with time.
	4.3.2. Maximum service temperature - dimensional stability	ST (+) 105°C

The performances of the product identified above is in conformity with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer.

ADCA is a frequently used chemical blowing agent, which decomposes during heat induced foaming processes commonly used to produce certain foams. Residual ADCA levels in those foams are typically very low, but not nil. In our production processes we take special care to ensure residual ADCA levels as low as technically feasible. Our rubber foams, produced at NMC Polska Sp. z o.o (Zabrze, Poland), show levels which exceed the 0.1 wt% threshold value. In alignment with REACH these grades have been notified and can be consulted in the SCIP database.

MCCP is commonly used as a plasticizer & flame retardant in rubber products. Although we are looking for alternatives, we confirm that all our current rubber foams, produced at NMC Polska Sp. z o.o (Zabrze, Poland), show levels which exceed the 0.1 wt% threshold value. In alignment with REACH these grades have been notified and can be consulted in the SCIP database.

If you are using or intend to use one or more of these grades, you may address all your ADCA & MCCP related questions to your commercial contact.

Signed for and on behalf of the manufacturer by:

**Name and function**

**Deputy Certification and Lab Coordinator**



**Izabela Blesińska**

Zabrze, 07-10-2022

\*this Declaration of Performance replaced DoP No. W4FEF901 of 18.11.2020