



INSUL ROLL

MATERIAL	INSUL ROLL is a flexible insulating material made of closed-cell foam based on rubber (rolled insulation).	
THERMAL CONDUCTIVITY (EN ISO 8497)	0,033 W/mK at - 50 °C 0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C	
TEMPERATURE RANGE (EN 14707)	-50 °C to +105 °C	
FIRE PERFORMANCE (EN 13501-1)	Bs3d0	
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≤ 25 mm: 10.000 μ ≥ 32 mm: 7.000 μ	
APPLICATION AREA	Heating and plumbing Cooling systems	Air conditioning Shipbuilding

ADVANTAGES

- Due to the very good thermal insulation properties, the energy input for the operation of air-conditioning and refrigeration systems as well as sanitary and heating installations can be significantly reduced
- Improvement of the economic and ecological efficiency of the entire unit
- Prevention of condensation
- Sound absorbing insulation for acoustic comfort
- Cut as needed
- Minimal cutting scrap

See website for Declaration of performance: www.nmc-insulation.com




NMC sa

Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

INSUL ROLL



Type	A mm	B mm	Length m	Pkg unit m ²
1000 x 6	1000	6	20	20
1000 x 9	1000	9	15	15
1000 x 13	1000	13	11	11
1000 x 16	1000	16	9	9
1000 x 19	1000	19	8	8
1000 x 25	1000	25	6	6
1000 x 32	1000	32	4	4
1000 x 40	1000	40	4	4
1000 x 50	1000	50	4	4