



# INSUL ROLL

cover silver

<b>MATERIAL</b>	INSUL ROLL cover silver is a flexible insulating material made of closed-cell foam based on rubber pre-covered with a synthetic-aluminium laminated foil (rolled insulation).
<b>THERMAL CONDUCTIVITY (EN ISO 8497)</b>	0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C
<b>TEMPERATURE RANGE (EN 14707)</b>	-30 °C to +95 °C
<b>TEMPERATURE RESISTANCE FOR JACKETING</b>	-25 °C up to 75 °C
<b>FIRE PERFORMANCE (EN 13501-1)</b>	Ds3d0
<b>WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)</b>	≤ 25 mm: 10.000 μ ≥ 32 mm: 7.000 μ
<b>APPLICATION AREA</b>	Air conditioning Cooling systems

See website for Declaration of performance: [www.nmc-insulation.com](http://www.nmc-insulation.com)



## NMC sa

Gert-Noël-Strasse · B-4731 Eynatten

Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55


E-Mail: [info@nmc.eu](mailto:info@nmc.eu)

[www.nmc-insulation.com](http://www.nmc-insulation.com)



# PRODUCT RANGE

## INSUL ROLL | cover silver



### ADVANTAGES

- Due to the very good thermal insulation, the energy input for the operation of air-conditioning and refrigeration systems as well as sanitary and heating installations can be significantly reduced
- Improvement of the economic and ecological efficiency of the entire unit
- Prevention of condensation
- Time and cost savings at the installation due to pre-coated insulation
- Long-term protection against condensation and energy loss
- Protecting against mechanical impacts
- Excellent UV-resistant
- Weatherproof
- Aesthetic surface in metallic which is suitable for both indoor and outdoor applications and is easy to clean
- Cut as needed
- Minimal cutting scrap

Type	A mm	B mm	Length m	Pkg unit m <sup>2</sup>
1000 x 6	1000	6	20	20
1000 x 9	1000	9	15	15
1000 x 13	1000	13	11	11
1000 x 16	1000	16	9	9
1000 x 19	1000	19	8	8
1000 x 25	1000	25	6	6
1000 x 32	1000	32	4	4