



INSUL ROLL

xt
cover silver

MATERIAL	INSUL ROLL xt cover silver is a flexible insulating material made of closed-cell foam based on rubber, with self-adhesive closing system and pre-covered with a synthetic-aluminium laminated foil (rolled insulation).
THERMAL CONDUCTIVITY (EN ISO 8497)	0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	-30 °C to +85 °C
TEMPERATURE RESISTANCE FOR JACKETING	-25 °C up to 75 °C
FIRE PERFORMANCE (EN 13501-1)	Ds3d0
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≤ 25 mm: 10.000 μ ≥ 32 mm: 7.000 μ
APPLICATION AREA	Air conditioning Cooling systems

See website for Declaration of performance: www.nmc-insulation.com



NMC (UK) LTD.

Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277


Email: enquiries@nmc-uk.com

www.nmc-insulation.com



PRODUCT RANGE

INSUL ROLL xt cover silver



ADVANTAGES

- Due to the very good thermal insulation properties, the energy input for the operation of air-conditioning and refrigeration systems as well as sanitary and heating installations can be significantly reduced
- Improvement of the economic and ecological efficiency of the entire unit
- Prevention of condensation
- Time and cost savings at the installation due to pre-coated insulation
- Long-term protection against condensation and energy loss
- Protecting against mechanical impacts
- Excellent UV-resistant
- Weatherproof
- Aesthetic surface in metallic which is suitable for both indoor and outdoor applications and is easy to clean
- Cut as needed
- Minimal cutting scrap
- Assembly time reduced up to 50 %

Type	A mm	B mm	Length m	Pkg unit m ²
1000 x 6	1000	6	20	20
1000 x 9	1000	9	15	15
1000 x 13	1000	13	11	11
1000 x 16	1000	16	9	9
1000 x 19	1000	19	8	8
1000 x 25	1000	25	6	6
1000 x 32	1000	32	4	4