



# AEROTAPE® (HT)

---

Flexible self-adhesive rubber tape (EPDM) for use in air conditioning and cooling systems.

- Synthetic rubber
- Dimensions: 3 mm x 50 mm (9,1 m and 15 m length)
- Colour: black

## Product features

- Thermal conductivity (EN ISO 12667):  
0,037 W/mK at 10°C  
0,040 W/mK at 40°C
- Water vapour diffusion resistance:  $\mu \geq 3000$
- Fire Performance: D-s3,d0 (EN 13501-1)
- Temperature range: Paperliner: -30°C to +93°C  
PO Liner: -50°C to 85°C
- Processing- and storage temperature: +15°C to +30°C
- Resistant to weather, UV and ozone
- Durability: 1 year
- Available with paper or polyolefin liner
  - Polyolefin liner is provided with reinforcing fabric



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

10/2021 responsible publisher: NMC sa,  
Gert-Noël-Strasse, B-4731 Eynatten [www.nmc-insulation.com](http://www.nmc-insulation.com)

---

**NMC sa**  
Gert-Noël-Strasse · B - 4731 Eynatten  
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55  
E-Mail: [info@nmc.eu](mailto:info@nmc.eu)  
[www.nmc-insulation.com](http://www.nmc-insulation.com)