



Marine & Offshore

Certificate number: 71972/A0 MED

File number: AC11360/037/004

Item number: MED/3.18d

This certificate is not valid when presented without the full attached schedule
composed of 7 sections
www.veristar.com

Notified Body 2690 - MARINE EQUIPMENT DIRECTIVE 2014/90/EU

EC TYPE EXAMINATION CERTIFICATE

as per Module B of Directive 2014/90/EU of the European Parliament and of the Council of 23 July 2014 as transposed in the French Regulations and Commission Implementing Regulation (EU) 2022/1157 of 4 July 2022

This certificate is issued to:

NMC Polska Sp. z o.o.

Zabrze - POLAND

for the type of product

SURFACE MATERIALS AND FLOOR COVERINGS WITH LOW FLAME-SPREAD CHARACTERISTICS: PIPE INSULATION COVERS

AEROFLEX® HF, AEROFLEX® HF ROLL, AEROFLEX® HF SHEET

Density (60 ± 5) kg/m³ - Thickness from 6 mm to 50 mm

Requirements:

SOLAS 74 convention as amended, Regulations II-2/3, II-2/5, II-2/6, II-2/9, X/3
IMO Res. MSC.36(63) -(1994 HSC Code)- as amended, 7
IMO Res. MSC.97(73) -(2000 HSC Code)- as amended, 7
IMO Res. MSC.307(88) (2010 FTP Code)
IMO MSC/Circ.1120

This certificate is issued on behalf of the French Maritime Authorities to attest that Bureau Veritas Marine & Offshore did undertake the relevant type-examination procedures for the product identified above which was found to comply with the relevant requirements of the Directive 2014/90/EU of the European Parliament and of the Council of 23 July 2014 as transposed in the French Regulations.

This certificate will expire on: 19 Dec 2027


For Bureau Veritas Marine & Offshore Notified Body 2690,

At BV KATOWICE, on 19 Dec 2022,

Wojciech Lubojanski

This certificate was created electronically and is valid without signature



This certificate does not allow to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark ) to the products corresponding to this type. To this end, the production-control phase module (D, E or F) of Annex II of the Directive is to be complied with and controlled by a written inspection agreement with a notified body.

This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. Bureau Veritas Marine & Offshore is designated by the French Maritime Authority as a "notified body" under the terms of the French Regulations Division 140 Chapter 140-2. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION:

AEROFLEX® HF, AEROFLEX® HF ROLL, AEROFLEX® HF SHEET

Black colored flexible closed-cell expanded EPDM halogen free foam insulation.

Nominal density: (60 ± 5) kg/m³.

Range of thickness: from 6 mm to 50 mm.

AEROFLEX® HF was tested glued on 1.5 mm steel sheet with adhesive type "AEROSEAL TF / HT" (application rate: 200~250 g/m²).

2. DOCUMENTS AND DRAWINGS:

2.1 - Technical data sheet "AEROFLEX® HF" dated 04/2019.

2.2 - NMC documents "Declaration of performance" both dated 15/06/2021.

3. TEST REPORTS:

3.1 - AEROFLEX® HF (thickness 6 mm; density 65 kg/m³):

Test report N° SL/Z-379/FTP5/0441a/2022, dated 28/06/2022, as per IMO 2010 FTP Code Annex 1 Part 5, from SYCHTA Laboratorium Sp. J., Poland.

3.2 - AEROFLEX® HF (thickness 50 mm; density 55 kg/m³):

Test report N° N° SL/Z-379/FTP5/0443a/2022, dated 28/06/2022, as per IMO 2010 FTP Code Annex 1 Part 5, from SYCHTA Laboratorium Sp. J., Poland.

4. APPLICATION / LIMITATION:

4.1 - The fitting aboard should be the same as used for the test.

4.2 - Approved material is considered as having low flame spread characteristics (as per IMO 2010 FTP Code Part 5).

4.3 - Approved for use as insulating material in refrigeration systems and chilled water piping for air-conditioning systems.

5. PRODUCTION SURVEY REQUIREMENTS:

5.1 - This certificate alone does not allow the applicant to issue the Declaration of Conformity and to affix the mark of conformity (wheelmark) to the products corresponding to this type. To this end, the production-control phase module D Production Quality Assurance or module E Product Quality Assurance or module F Product Verification of Annex II of the Directive is to be complied with and controlled by a written inspection agreement with a Notified Body.

5.2 - For information concerning the production phase modules, **NMC Polska Sp. z o.o.** has declared the following manufacturing site:

**AEROFLEX Co., Ltd.
111/7, 111/11 M.2, T. Makamuku
A. Nikompattana, Rayong 21180
THAILAND**

6. MARKING OF PRODUCT:

Reference is made to MED 2014/90/EU chapter 2.

In particular Article 10.3 specifies that the wheelmark shall be followed by the identification number of the Notified Body involved in the production control phase (module D, E or F) and by the year in which the mark is affixed (4 digits or last 2 digits).

7. OTHERS:

It is **NMC Polska Sp. z o.o.**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

*** END OF CERTIFICATE ***