



AEROLINE®

inox split 100

SHEATHING

MATERIAL	Polyolefin film
	Very good ozone resistance, UV-resistant

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No.1.4404 (AISI 316L)
TEMPERATURE RANGE	-270 °C to 600 °C
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C	DN 16: 7,9 bar DN 20: 7,9 bar DN 25: 4,9 bar

SENSOR CABLE

2 x 0,75 mm² VDE 7507

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber. Free of PVC and CFC (according to legal requirements). No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
TEMPERATURE RANGE	+150 °C, short-term up to +175 °C (stagnation temperature of collectors)
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE® | inox split 100

Reference	SAP	Length (m)
DN 16		
16 x 17/10 m	3055659	10
16 x 17/15 m	3055660	15
16 x 17/20 m	3055661	20
16 x 17/25 m	3055662	25
16 x 17/50 m	3055663	50
DN 20		
20 x 18/10 m	3055669	10
20 x 18/15 m	3055670	15
20 x 18/20 m	3055671	20
20 x 18/25 m	3055672	25
20 x 18/50 m	3055673	50
DN 25		
25 x 25/10 m	3055674	10
25 x 25/15 m	3055675	15
25 x 25/20 m	3055676	20
25 x 25/25 m	3055677	25
25 x 25/50 m	3055678	50