



AEROLINE®

inox connect 200

SHEATHING

MATERIAL	Additional EPDM insulation with surface protection
UV RESISTANCE	Excellent
OZONE RESISTANCE	Excellent

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C	DN 25: 12 bar DN 32: 6,5 bar

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic Rubber No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox connect 200

Reference	SAP	Length (m)
PEX 25		
25 x 76/1 m	3053309	2
25 x 76/1,3 m	3053310	2,6
DN 32		
32 x 76/1 m	3053311	2
32 x 76/1,3 m	3053312	2,6

