



AEROLINE®

inox eco

SHEATHING

MATERIAL	Polyolefin film
	Very good ozone resistance, UV-resistant

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
TEMPERATURE RANGE	-270 °C to 600 °C
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C	DN 16: 7,9 bar DN 20: 7,9 bar DN 25: 4,9 bar

SENSOR CABLE

2 x 0,75 mm² VDE 7507

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber. Free of PVC and CFC (according to legal requirements). No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
TEMPERATURE RANGE	+150 °C, short-term up to +175 °C
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox eco

Reference	SAP	Length (m)
DN 16		
16 x 13/10 m	3042647	10
16 x 13/15 m	3042648	15
16 x 13/20 m	3042649	20
16 x 13/25 m	3042650	25
16 x 13/50 m	3056390	50
DN 20		
20 x 13/10 m	3042651	10
20 x 13/15 m	3042652	15
20 x 13/20 m	3042653	20
20 x 13/25 m	3042654	25
20 x 13/50 m	3056391	50
DN 25		
25 x 13/10 m	3042168	10
25 x 13/15 m	3042169	15
25 x 13/20 m	3042655	20
25 x 13/25 m	3042170	25
25 x 13/50 m	3056392	50