



AEROLINE®

inox pro 100

SHEATHING

MATERIAL	Mounting protection made from robust polyester/stainless steel wire mesh
UV RESISTANCE	Excellent
OZONE RESISTANCE	Excellent

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
TEMPERATURE RANGE	-270 °C to 600 °C
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C	DN 16: 7,9 bar DN 20: 7,9 bar

SENSOR CABLE

3 x 0,75 mm² VDE 0295, Silicone, Class 5

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox pro 100

Reference	SAP	Length (m)
DN 16		
16 x 17/10 m	3055654	10
16 x 17/15 m	3055655	15
16 x 17/20 m	3055656	20
16 x 17/25 m	3055657	25
16 x 17/50 m	3055658	50
DN 20		
20 x 18/10 m	3055664	10
20 x 18/15 m	3055665	15
20 x 18/20 m	3055666	20
20 x 18/25 m	3055667	25
20 x 18/50 m	3055668	50