



# AEROLINE®

## inox rapid classic

### SHEATHING

---

MATERIAL Polyolefin foil

### STAINLESS STEEL CORRUGATED PIPE

---

MATERIAL Material No. 1.4404 (AISI 316L)

MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C  
DN 25: 6 bar  
DN 32: 6,5 bar  
DN 40: 5,8 bar

MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C  
DN 16: 7,9 bar      DN 32: 5,5 bar  
DN 20: 7,9 bar      DN 40: 4,9 bar  
DN 25: 4,9 bar

### INSULATION MADE OF EPDM

---

MATERIAL Light, flexible, closed-cell, synthetic Rubber.  
No embrittlement of copper and stainless steel pipes  
(DIN 1988 Part 200)  
Dimensions and tolerances according to DIN EN 14304

THERMAL CONDUCTIVITY  
0,036 W/mK at 0 °C  
0,038 W/mK at 40 °C

FIRE BEHAVIOUR Euro class E (DIN EN 13501-1)

TEMPERATURE RANGE (EN 14707) +150 °C (short-term up to +175 °C)



**NMC sa**  
Gert-Noël-Strasse · B-4731 Eynatten  
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55  
E-Mail: [info@nmc.eu](mailto:info@nmc.eu)  
[www.nmc-insulation.com](http://www.nmc-insulation.com)



# PRODUCT RANGE

## AEROLINE®

inox rapid classic

Reference	SAP	Length (m)
<b>DN 16</b>		
16 x 13/10 m	3032601	10
16 x 13/25 m	3032602	25
16 x 13/50 m	3032603	50
16 x 25/10 m	3032604	10
16 x 25/25 m	3032605	25
16 x 25/50 m	3032606	50
<b>DN 20</b>		
20 x 13/10 m	3032607	10
20 x 13/25 m	3032609	25
20 x 13/50 m	3032610	50
20 x 25/10 m	3032611	10
20 x 25/25 m	3032613	25
20 x 25/50 m	3032614	50
<b>DN 25</b>		
25 x 19/5 m	3053313	5
25 x 19/10 m	3032616	10
25 x 19/25 m	3032618	25
25 x 19/50 m	3032619	50
<b>DN 32</b>		
32 x 19/5 m	3053314	5
32 x 19/10 m	3032651	10
32 x 19/25 m	3032654	25
<b>DN 40</b>		
40 x 25/5 m	3053315	5
40 x 25/10 m	3032688	10
40 x 25/25 m	3032689	25