



AEROLINE®

inox rapid pro gs

SHEATHING

MATERIAL	Polyester braid
UV RESISTANCE	Excellent
OZONE RESISTANCE	Excellent

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C	DN 25: 6 bar DN 32: 6,5 bar DN 40: 5,8 bar
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C	DN 25: 4,9 bar DN 32: 5,5 bar DN 40: 4,9 bar

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic Rubber No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)
TEMPERATURE RANGE (EN 14707)	+150 °C (short-term up to +175 °C)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox rapid progs

Reference	SAP	Length (m)
DN 25		
25 x 19/5 m	3053138	5
25 x 19/10 m	3032250	10
25 x 19/25 m	3032251	25
25 x 38/5 m	3053316	5
25 x 38/10 m	3032253	10
25 x 38/25 m	3032254	25
DN 32		
32 x 19/5 m	3053317	5
32 x 19/10 m	3032255	10
32 x 19/25 m	3032256	25
32 x 38/5 m	3053318	5
32 x 38/10 m	3032257	10
32 x 38/25 m	3032258	25
DN 40		
40 x 25/5 m	3053319	5
40 x 25/10 m	3032259	10
40 x 25/25 m	3032260	25