



AEROLINE®

inox rapid pro

SHEATHING

MATERIAL	Mounting protection made from strong polyester fabric / stainless steel wire
	Very good ozone resistance, UV-resistant

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
TEMPERATUREINSATZBEREICH	-270 °C to 600 °C
MAXIMUM PERMISSIBLE	DN 16: 7,9 bar
OPERATING PRESSURE AT 200°C	DN 20: 7,9 bar

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber. Free of PVC and CFC (according to legal requirements). No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
TEMPERATURE RANGE	+150 °C, short-term up to +175 °C (stagnation temperature of collectors)
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE® | inox rapid pro

Reference	SAP	Length (m)
DN 16		
16 x 13/10 m	3032236	10
16 x 13/25 m	3032237	25
16 x 13/50 m	3032238	50
16 x 25/10 m	3032261	10
16 x 25/25 m	3032262	25
16 x 25/45 m	3032263	45
DN 20		
20 x 13/10 m	3032244	10
20 x 13/25 m	3032246	25
20 x 13/50 m	3032247	50
20 x 25/10 m	3032264	10
20 x 25/25 m	0302266	25
20 x 25/45 m	3032267	45