

AEROLINE®

inox terra

JACKET PIPE

MATERIAL	Double-walled cable protection pipe with smooth inner wall made of PE-HD
RING STIFFNESS	Ring stiffness according to DIN 16961, SN24 ≥ 16.0 kN/m²
OUTER DIAMETER	200 mm
MINIMUM BENDING RADIUS	50 cm

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C	DN 32: 6,5 bar DN 40: 5,8 bar

ELECTRICAL INSTALLATION PIPE 32

INNER DIAMETER	25 mm (DIN EN 50086): for control, sensor or electrical load cables

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber. Does not cause embrittlement of copper or stainless steel pipes in accordance with DIN 1988-200. Dimensions and tolerances based on DIN EN 14304. DN 32: DL 25 mm / RL 19 mm DN 40: DL 19 mm / RL 19 mm
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)

INCLUDED ACCESSORIES

BENDING AID	Strap to facilitate a fixed bend
ROUTE WARNING TAPE	One red and one yellow route warning tape

LRQA CERTIFIED
ISO 9001 · ISO 14001
ISO 45001

NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com

nmc

PRODUCT RANGE

AEROLINE® | inox terra

Reference	SAP	Length (m)
DN 32		
DN 32, length 3 m	3057817	3
DN 32, length 5 m	3032659	5
DN 32, length 7,5 m	3032660	7,5
DN 32, length 10 m	3032661	10
DN 32, length 12 m	3032662	12
DN 32, length 14 m	3032663	14
DN 32, length 17,5 m	3032664	17,5
DN 32, length 20 m	3032665	20
DN 32, length 25 m	3032666	25
DN 40		
DN 40, length 3 m	3057818	3
DN 40, length 5 m	3032693	5
DN 40, length 7,5 m	3032694	7,5
DN 40, length 10 m	3032695	10
DN 40, length 12 m	3032696	12
DN 40, length 14 m	3032697	14
DN 40, length 17,5 m	3032698	17,5

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ACESSORIES
AEROLINE® | inox terra

Basic Accessory Set



Description	Reference	SAP	Set/CAR	
2x Rubber end cap 200 mm 1x Connection set	DN 32	3059489	1	
	DN 40	3059490	1	

Premium Accessory Set



Description	Reference	SAP	Set/CAR	
2x Rubber end cap 200 mm 1x Connection set 1x Masonry sealing sett	DN 32	3059491	1	
	DN 40	3059492	1	

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
08/2026 responsible publisher: NMC sa · Gert-Noël-Strasse · B-4731 Eynatten · www.nmc-insulation.com

ACESSORIES

AEROLINE® | inox terra



Masonry sealing set

Description	Reference	SAP	Pc./📦	RBG
Sealing insert made of stainless steel and EPDM rubber; 5 stainless steel clip rings for 200 mm jacket pipe (250 mm core drill hole).	DN 32/40	3032583	1	AS5



Jacket pipe sealing set

Description	Reference	SAP	Pc./📦	RBG
For air- and watertight sealing of the jacket pipe and the fixed support of the stainless steel corrugated pipes.	DN 32	3032658	1	AS5
	DN 40	3032692	1	AS5



Connection set

Description	Reference	SAP	Pc./📦	RBG
For the connection to the heating pump and heating system.	DN 32	3032153	1	AS1
	DN 40	3032154	1	AS1



Double nipple

Description	Reference	SAP	Pc./📦	RBG
1½" x 1½" for DN 32 / 2" x 2" for DN 40	1½" x 1½"	3032929	1	AS1
	2" x 2"	3032930	1	AS1



Reducing nipple

Description	Reference	SAP	Pc./📦	RBG
Male thread	1½" x 1¼" AG	3032969	1	AS1
	2" x 1½" AG	3032970	1	AS1



Reducing piece

Description	Reference	SAP	Pc./📦	RBG
Male thread / female thread	1½" x 1¼	3032973	1	AS1
	2" x 1½"	3032974	1	AS1

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert-Noël-Strasse · B-4731 Eynatten · www.nmc-insulation.com