



AEROLINE®

pex terra

JACKET PIPE

MATERIAL	Double-walled cable protection pipe with smooth inner wall made of PE-HD
RING STIFFNESS	Ring stiffness according to DIN 16961, SN24 $\geq 16.0 \text{ kN/m}^2$
OUTER DIAMETER	160 mm
MINIMUM BENDING RADIUS	42,5 cm

CARRIER PIPE

MATERIAL	PE-Xa
DEGREE OF CROSS-LINKING	$\geq 70 \%$ (EN ISO 15875)
OXYGEN DENSITY	according to DIN 4726
TEMPERATURE RANGE	up to 90 °C
MAXIMUM PERMISSIBLE	6 bar
OPERATING PRESSURE AT 95 °C	
COEFFICIENT OF LINEAR EXPANSION	at 20 °C: $1,4 \cdot 10^{-4} \text{ 1/k}$ at 100 °C: $2,05 \cdot 10^{-4} \text{ 1/k}$

ELECTRICAL INSTALLATION PIPE 32

INNER DIAMETER	25 mm (DIN EN 50086) for control, sensor or electrical load cables
----------------	---

INSULATION MADE OF POLYETHYLENE

MATERIAL	Flexible insulation made of foamed, closed-cell polyethylene with recycled materials Dimensions and tolerances in accordance with DIN EN 14303 PEX 25 / PEX 32: 20 mm PEX 40: 13 mm
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C
FIRE BEHAVIOUR	C _L -s1,d0 (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

p e x t e r r a

Reference	SAP	Length (m)
PEX 25 x 2,3		
PEX 25, length 3 m	3052800	3
PEX 25, length 5 m	3052801	5
PEX 25, length 7,5 m	3052802	7,5
PEX 25, length 10 m	3052803	10
PEX 25, length 12 m	3052804	12
PEX 25, length 14 m	3052805	14
PEX 25, length 17,5 m	3052806	17,5
PEX 25, length 20 m	3052807	20
PEX 25, length 25 m	3052808	25
PEX 32 x 2,9		
PEX 32, length 3 m	3052809	3
PEX 32, length 5 m	3052810	5
PEX 32, length 7,5 m	3052811	7,5
PEX 32, length 10 m	3052812	10
PEX 32, length 12 m	3052813	12
PEX 32, length 14 m	3052814	14
PEX 32, length 17,5 m	3052815	17,5
PEX 32, length 20 m	3052816	20
PEX 32, length 25 m	3052817	25
PEX 40 x 3,7		
PEX 40, length 3 m	3052818	3
PEX 40, length 5 m	3052819	5
PEX 40, length 7,5 m	3052820	7,5
PEX 40, length 10 m	3052821	10
PEX 40, length 12 m	3052822	12
PEX 40, length 14 m	3052823	14
PEX 40, length 17,5 m	3052824	17,5
PEX 40, length 20 m	3052825	20
PEX 40, length 25 m	3052826	25