



AEROFLEX®

sh coil

MATERIAL	AEROFLEX® sh coil is a flexible insulation made of black closed-cell EPDM supplied as a continuous tube on a roll.
LENGTH	16 to 30 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,035 W/mK at 10 °C 0,038 W/mK at 40 °C
TEMPERATURE RANGE (EN 14707)	Up to 110 °C
FIRE PERFORMANCE (EN 13501-1)	C _s d0
APPLICATION AREA	Heating and plumbing
ADVANTAGES	▪ Limited smoke generation to meet enhanced fire safety requirements (EN 13501-1). ▪ High thermal insulation performance to reduce heat loss in building services and industrial installations. ▪ Sound-insulating properties help reduce operating and flow noise. ▪ Continuous tube format for flexible length adjustment according to project requirements. ▪ Reduced material waste through precise cutting. ▪ Fewer bonded joints for more efficient installation and a clean insulation finish.

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
 Gert-Noël-Strasse · B-4731 Eynatten
 Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
 E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROFLEX®

sh coil



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm	A mm	B mm	Pkg unit m
15 x 10	10	15	8	13,5	1/4	-	15	12	30
18 x 10	15	18	10	17,2	3/8	16	18	12	30
22 x 10	20	22	15	21,3	1/2	20	22	12	22
28 x 10	25	28	20	26,9	3/4	25	28	12	16