

AEROFLEX® (ht)

MATERIAL	AEROFLEX® (ht) is a highly flexible insulation made from black, closed-cell EPDM for demanding temperature applications.
LENGTH	2 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,036 W/mK at 0 °C 0,037 W/mK at 10 °C 0,038 W/mK at 40 °C
TEMPERATURE RANGE (EN 14707)	-50 °C to 150 °C (continuous operation – Peak usage up to 175 °C)Flexible down to -50 °C, but can be used up to -200 °C
FIRE PERFORMANCE (EN 13501-1)	C_L-s2,d0
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≥ 3.000 µ
APPLICATION AREA	Thermal solar module Industry Air conditioning Shipbuilding High temperatures Heating and plumbing Cooling systems

ADVANTAGES

- High temperature resistance for applications exposed to continuously elevated or fluctuating temperatures.
- Excellent resistance to UV radiation, ozone and weathering for long-term indoor and outdoor use.
- Closed-cell material structure that limits moisture absorption and helps reduce condensation formation.
- UL certified.
- Marine approval for use in maritime applications.

See website for Declaration of performance: www.nmc-insulation.com

CE


LRQA CERTIFIED

NMC (UK) LTD.
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

nmc

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
6 x 6	4	6	-	-	-	-	6	6	360
8 x 6	-	8	-	-	-	-	8	6	320
10 x 6	8	10	6	10,2	1/8	-	10	6	280
12 x 6	10	12	-	-	-	-	12	6	220
15 x 6	10	15	8	13,5	1/4	-	15	6	160
18 x 6	15	18	10	17,2	3/8	16	18	6	140
22 x 6	20	22	15	21,3	1/2	20	22	6	140
25 x 6	25	28	20	26,9	3/4	25	25	6	120
28 x 6	25	28	20	26,9	3/4	28	28	6	100
32 x 6	-	-	-	-	1	32	32	6	80
35 x 6	32	35	25	33,7	1	32	35	6	80
42 x 6	40	42	32	42,4	1 1/4	40	42	6	60
45 x 6	-	-	40	48,3	1 1/2	-	45	6	56
48 x 6	-	-	40	48,3	1 1/2	40,2	48	6	48
6 x 9	4	6	-	-	-	-	6	9	264
8 x 9	-	8	-	-	-	-	8	9	220
10 x 9	8	10	6	10,2	1/8	-	10	9	220
12 x 9	10	12	-	-	-	-	12	9	168
15 x 9	10	15	8	13,5	1/4	-	15	9	140
18 x 9	15	18	10	17,2	3/8	16	18	9	120
22 x 9	20	22	15	21,3	1/2	20	22	9	108
25 x 9	25	28	20	26,9	3/4	25	25	9	88
28 x 9	25	28	20	26,9	3/4	25	28	9	72
32 x 9	-	-	-	-	1	32	32	9	68
35 x 9	32	35	25	33,7	1	32	35	9	64
42 x 9	40	42	32	42,4	1 1/4	40	42	9	56
45 x 9	-	-	40	48,3	1 1/2	-	45	9	48
48 x 9	-	-	40	48,3	1 1/2	40,2	48	9	40
54 x 9	50	54	-	54	-	50	54	9	36
57 x 9	-	-	-	-	-	-	57	9	36

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
60 x 9	-	-	50	60,3	2	-	60	9	36
64 x 9	-	64	-	63,5	-	63	64	9	32
70 x 9	-	-	-	-	-	-	70	9	20
76 x 9	65	76,1	65	76,1	2 1/2	-	76	9	20
90 x 9	-	-	-	-	-	-	90	9	16
102 x 9	-	-	-	101,6	3 1/2	-	102	9	16
109 x 9	-	-	-	-	-	-	109	9	12
115 x 9	-	-	-	-	-	-	115	9	12
125 x 9	-	-	-	125	-	-	125	9	12
130 x 9	-	-	-	-	-	-	130	9	8
140 x 9	-	-	125	139,7	5	-	140	9	8
165 x 9	-	-	-	-	-	-	165	9	8
6 x 13	4	6	-	-	-	-	6	13	160
8 x 13	-	8	-	-	-	-	8	13	140
10 x 13	8	10	6	10,2	1/8	-	10	13	140
12 x 13	10	12	-	-	-	-	12	13	120
15 x 13	10	15	8	13,5	1/4	-	15	13	100
18 x 13	15	18	10	17,2	3/8	16	18	13	80
22 x 13	20	22	15	21,3	1/2	20	22	13	64
25 x 13	25	28	20	26,9	3/4	25	25	13	60
28 x 13	25	28	20	26,9	3/4	25	28	13	56
32 x 13	-	-	-	-	1	32	32	13	48
35 x 13	32	35	25	33,7	1	32	35	13	40
42 x 13	40	42	32	42,4	1 1/4	40	42	13	36
45 x 13	-	-	40	48,3	1 1/2	-	45	13	36
48 x 13	-	-	40	48,3	1 1/2	40,2	48	13	32
54 x 13	50	54	-	54	-	50	54	13	28
57 x 13	-	-	-	-	-	-	57	13	28
60 x 13	-	-	50	60,3	2	-	60	13	24
64 x 13	-	64	-	63,5	-	63	64	13	20

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
70 x 13	-	-	-	-	-	-	70	13	20
76 x 13	65	76,1	65	76,1	2 1/2	-	76	13	16
90 x 13	-	-	-	-	-	-	90	13	16
102 x 13	-	-	-	101,6	3 1/2	-	102	13	16
109 x 13	-	-	-	-	-	-	109	13	12
115 x 13	-	-	-	-	-	-	115	13	12
125 x 13	-	-	-	125	-	-	125	13	8
130 x 13	-	-	-	-	-	-	130	13	8
140 x 13	-	-	125	139,7	5	-	140	13	8
165 x 13	-	-	-	-	-	-	165	13	8
6 x 19	4	6	-	-	-	-	6	19	64
8 x 19	-	8	-	-	-	-	8	19	64
10 x 19	8	10	6	10,2	1/8	-	10	19	64
12 x 19	10	12	-	-	-	-	12	19	64
15 x 19	10	15	8	13,5	1/4	-	15	19	56
18 x 19	15	18	10	17,2	3/8	16	18	19	48
22 x 19	20	22	15	21,3	1/2	20	22	19	40
25 x 19	25	28	20	26,9	3/4	25	25	19	36
28 x 19	25	28	20	26,9	3/4	25	28	19	36
32 x 19	-	-	-	-	1	32	32	19	36
35 x 19	32	35	25	33,7	1	32	35	19	32
42 x 19	40	42	32	42,4	1 1/4	40	42	19	24
45 x 19	-	-	40	48,3	1 1/2	-	45	19	20
48 x 19	-	-	40	48,3	1 1/2	40,2	48	19	20
54 x 19	50	54	-	54	-	50	54	19	16
57 x 19	-	-	-	-	-	-	57	19	16
60 x 19	-	-	50	60,3	2	-	60	19	16
64 x 19	-	64	-	63,5	-	63	64	19	16
70 x 19	-	-	-	-	-	-	70	19	12
76 x 19	65	76,1	65	76,1	2 1/2	-	76	19	12

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
90 x 19	-	-	-	-	-	-	90	19	12
102 x 19	-	-	-	101,6	3 1/2	-	102	19	8
109 x 19	-	-	-	-	-	-	109	19	8
115 x 19	-	-	-	-	-	-	115	19	8
125 x 19	-	-	-	125	-	-	125	19	8
130 x 19	-	-	-	-	-	-	130	19	8
140 x 19	-	-	125	139,7	5	-	140	19	8
165 x 19	-	-	-	-	-	-	165	19	4
6 x 25	4	6	-	-	-	-	6	25	48
10 x 25	8	10	6	10,2	1/8	-	10	25	48
12 x 25	10	12	-	-	-	-	12	25	40
15 x 25	10	15	8	13,5	1/4	-	15	25	36
18 x 25	15	18	10	17,2	3/8	16	18	25	36
22 x 25	20	22	15	21,3	1/2	20	22	25	32
25 x 25	25	28	20	26,9	3/4	25	25	25	24
28 x 25	25	28	20	26,9	3/4	25	28	25	24
32 x 25	-	-	-	-	1	32	32	25	24
35 x 25	32	35	25	33,7	1	32	35	25	20
42 x 25	40	42	32	42,4	1 1/4	40	42	25	16
45 x 25	-	-	40	48,3	1 1/2	-	45	25	16
48 x 25	-	-	40	48,3	1 1/2	40,2	48	25	16
54 x 25	50	54	-	54	-	50	54	25	16
57 x 25	-	-	-	-	-	-	57	25	16
60 x 25	-	-	50	60,3	2	-	60	25	12
64 x 25	-	64	-	63,5	-	63	64	25	12
70 x 25	-	-	-	-	-	-	70	25	16
76 x 25	65	76,1	65	76,1	2 1/2	-	76	25	16
90 x 25	-	-	-	-	-	-	90	25	12
102 x 25	-	-	-	101,6	3 1/2	-	102	25	12
109 x 25	-	-	-	-	-	-	109	25	12

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
115 x 25	-	-	-	-	-	-	115	25	10
130 x 25	-	-	-	-	-	-	130	25	8
140 x 25	-	-	125	139,7	5	-	140	25	8
165 x 25	-	-	-	-	-	-	165	25	6
15 x 32	10	15	8	13,5	1/4	-	15	32	28
18 x 32	15	18	10	17,2	3/8	16	18	32	24
22 x 32	20	22	15	21,3	1/2	20	22	32	24
25 x 32	25	28	20	26,9	3/4	25	25	32	20
28 x 32	25	28	20	26,9	3/4	25	28	32	16
32 x 32	-	-	-	-	1	32	32	32	16
35 x 32	32	35	25	33,7	1	32	35	32	16
42 x 32	40	42	32	42,4	1 1/4	40	42	32	16
45 x 32	-	-	40	48,3	1 1/2	-	45	32	16
48 x 32	-	-	40	48,3	1 1/2	40,2	48	32	12
54 x 32	50	54	-	54	-	50	54	32	12
57 x 32	-	-	-	-	-	-	57	32	12
60 x 32	-	-	50	60,3	2	-	60	32	8
64 x 32	-	64	-	63,5	-	63	64	32	8
70 x 32	-	-	-	-	-	-	70	32	12
76 x 32	65	76,1	65	76,1	2 1/2	-	76	32	12
90 x 32	-	-	-	-	-	-	90	32	12
102 x 32	-	-	-	101,6	3 1/2	-	102	32	4
109 x 32	-	-	-	-	-	-	109	32	4
115 x 32	-	-	-	-	-	-	115	32	4
130 x 32	-	-	-	-	-	-	130	32	6
140 x 32	-	-	125	139,7	5	-	140	32	6
165 x 32	-	-	-	-	-	-	165	32	4
15 x 38	10	15	8	13,5	1/4	-	15	38	16
18 x 38	15	18	10	17,2	3/8	16	18	38	16
22 x 38	20	22	15	21,3	1/2	20	22	38	16

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® (ht)




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
25 x 38	25	28	20	26,9	3/4	25	25	38	16
28 x 38	25	28	20	26,9	3/4	25	28	38	16
32 x 38	-	-	-	-	1	32	32	38	16
35 x 38	32	35	25	33,7	1	32	35	38	12
42 x 38	40	42	32	42,4	1 1/4	40	42	38	12
45 x 38	-	-	40	48,3	1 1/2	-	45	38	12
48 x 38	-	-	40	48,3	1 1/2	40,2	48	38	12
54 x 38	50	54	-	54	-	50	54	38	8
57 x 38	-	-	-	-	-	-	57	38	8
60 x 38	-	-	50	60,3	2	-	60	38	8
64 x 38	-	64	-	63,5	-	63	64	38	8
70 x 38	-	-	-	-	-	-	70	38	6
76 x 38	65	76,1	65	76,1	2 1/2	-	76	38	6
90 x 38	-	-	-	-	-	-	90	38	10
102 x 38	-	-	-	101,6	3 1/2	-	102	38	4
109 x 38	-	-	-	-	-	-	109	38	6
115 x 38	-	-	-	-	-	-	115	38	6
130 x 38	-	-	-	-	-	-	130	38	4
140 x 38	-	-	125	139,7	5	-	140	38	4
165 x 38	-	-	-	-	-	-	165	38	4
22 x 50	20	22	15	21,3	1/2	20	22	50	8
25 x 50	25	28	20	26,9	3/4	25	25	50	8
28 x 50	25	28	20	26,9	3/4	25	28	50	8
32 x 50	-	-	-	-	1	32	32	50	8
35 x 50	32	35	25	33,7	1	32	35	50	8
42 x 50	40	42	32	42,4	1 1/4	40	42	50	8
45 x 50	-	-	40	48,3	1 1/2	-	45	50	8
48 x 50	-	-	40	48,3	1 1/2	40,2	48	50	6
54 x 50	50	54	-	54	-	50	54	50	6
57 x 50	-	-	-	-	-	-	57	50	6

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

AEROFLEX® | (ht)



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
60 x 50	-	-	50	60,3	2	-	60	50	6
64 x 50	-	64	-	63,5	-	63	64	50	6
70 x 50	-	-	-	-	-	-	70	50	4
76 x 50	65	76,1	65	76,1	2 1/2	-	76	50	4
90 x 50	-	-	-	-	-	-	90	50	4
102 x 50	-	-	-	101,6	3 1/2	-	102	50	4
109 x 50	-	-	-	-	-	-	109	50	4
115 x 50	-	-	-	-	-	-	115	50	4
130 x 50	-	-	-	-	-	-	130	50	4
140 x 50	-	-	125	139,7	5	-	140	50	4
165 x 50	-	-	-	-	-	-	165	50	4

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com