

AEROFLEX® | (ht) roll

MATERIAL	Highly flexible insulation in rolls made from black, closed-cell EPDM for demanding temperature applications.
THERMAL CONDUCTIVITY (EN ISO 8497)	0,036 W/mK at 0 °C 0,037 W/mK at 10 °C 0,040 W/mK at 40 °C
TEMPERATURE RANGE (EN 14707)	-50 °C to +150 °C (continuous operation - Peak usage up to 175 °C). Flexible down to -50 °C, but can be used up to -200 °C
FIRE PERFORMANCE (EN 13501-1)	D-s3,d0
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≥ 3.000 µ
APPLICATION AREA	Thermal solar module Industry Air conditioning Shipbuilding High temperatures Heating and plumbing Cooling systems
ADVANTAGES	▪ High temperature resistance for applications exposed to continuously elevated or fluctuating temperatures. ▪ Excellent resistance to UV radiation, ozone and weathering for long-term indoor and outdoor use. ▪ Closed-cell material structure that limits moisture absorption and helps reduce condensation formation. ▪ Enables application-specific cutting and helps reduce material waste. ▪ UL certified. ▪ Marine approval for use in maritime applications.

See website for Declaration of performance: www.nmc-insulation.com

CE


LRQA CERTIFIED

NMC (UK) LTD.
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

nmc

PRODUCT RANGE

AEROFLEX® | (ht) roll



Type	A mm	B mm	Length m	Pkg unit m^2
1000 x 3	1000	3	45	45
1000 x 6	1000	6	22	22
1000 x 9	1000	9	15	15
1000 x 13	1000	13	11	11
1000 x 16	1000	16	10	10
1000 x 19	1000	19	7	7
1000 x 25	1000	25	5	5
1000 x 32	1000	32	4	4
1000 x 38	1000	38	3	3

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com