



CLIMAFLEX®

naturefoam
stabil

MATERIAL	CLIMAFLEX® naturefoam stabil is a flexible insulating material made of foamed, closed-cell polyethylene containing at least 30% recycled and massbalanced raw materials, equipped with a robust protective coating.
LENGTH	2 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C 0,043 W/mK at 60 °C 0,045 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +100 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Heating and plumbing

ADVANTAGES

- Professional thermal insulation for significant energy savings
- Significantly improved CO₂ balance due to the use of recycled raw materials
- Improvement of the economic and ecological efficiency of the entire unit
- Equipped with a robust coating which offers protection against damage through the entire construction phase



See website for Declaration of performance: www.nmc-insulation.com



NMC (UK) LTD.

Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277

Email: enquiries@nmc-uk.com


www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX®

naturefcom
stabil



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW	Outer Ø	NW	Outer Ø		Outer Ø			
	DN	mm	DN	mm	inch	mm			
12/15 x 9	10	15	8	13,5	1/4	-	12/15	9	120
18 x 9	15	18	10	17,2	3/8	16	18	9	120
22 x 9	20	22	15	21,3	1/2	20	22	9	100
28 x 9	25	28	20	26,9	3/4	25	28	9	90
35 x 9	32	35	25	33,7	1	32	35	9	60
42 x 9	40	42	32	42,4	1 1/4	40	42	9	48
12/15 x 13	10	15	8	13,5	1/4	-	12/15	13	100
18 x 13	15	18	10	17,2	3/8	16	18	13	96
22 x 13	20	22	15	21,3	1/2	20	22	13	80
28 x 13	25	28	20	26,9	3/4	25	28	13	64
35 x 13	32	35	25	33,7	1	32	35	13	48
42 x 13	40	42	32	42,4	1 1/4	40	42	13	40
12/15 x 20	10	15	8	13,5	1/4	-	12/15	20	58
18 x 20	15	18	10	17,2	3/8	16	18	20	56
22 x 20	20	22	15	21,3	1/2	20	22	20	48
28 x 20	25	28	20	26,9	3/4	25	28	20	40
35 x 20	32	35	25	33,7	1	32	35	20	32
42 x 20	40	42	32	42,4	1 1/4	40	42	20	24
12/15 x 25	10	15	8	13,5	1/4	-	12/15	25	40
18 x 25	15	18	10	17,2	3/8	16	18	25	38
22 x 25	20	22	15	21,3	1/2	20	22	25	36
28 x 25	25	28	20	26,9	3/4	25	28	25	30
35 x 25	32	35	25	33,7	1	32	35	25	26
42 x 25	40	42	32	42,4	1 1/4	40	42	25	24