



CLIMAFLEX®

silence

MATERIAL	CLIMAFLEX® silence is a sound damping tube made of closed-cell foam based on polyethylene with a robust outer skin.
LENGTH	10 m
TEMPERATURE RANGE (EN 14707)	Up to +95 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
SOUND PRESSURE LEVEL REDUCTION	Up to 20dB(A) according to DIN 4109 and EN 14366 with a water flow of 1L/s and 2L/s and a pipe diameter of DN100 (cast iron pipe).
APPLICATION AREA	Cast iron and plastic waste water pipes Ventilation pipes

ADVANTAGES

- Inner gliding foil for easy pipe covering
- Protection against damage
- Sound damping for plastic and metal pipes
- Corrosion protection for metal pipes




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX® | silence



Type	Plastic waste water pipes		Cast iron waste water pipes		A mm	B mm	Pkg unit m
	NW DN	Outer Ø * mm	NW DN	Outer Ø ** mm			
50 x 4	50	63	-	-	70 ±3	4	110
60 x 4	-	-	-	-	72 ±3	4	80
70 x 4	65	75	70	78	92 ±3	4	80
80 x 4	80	90	-	-	100 ±3	4	70
90 x 4	80	90	-	-	112 ±4	4	60
100 x 4	100	110	100	110	125 ±4	4	50
125 x 4	125	125	125	135	148 ±4	4	40
136 x 4	-	-	-	-	160 ±5	4	40
150 x 4	150	160	150	160	180 ±5	4	30
50 x 9	50	63	-	-	70 ±5	9	40
70 x 9	65	75	70	78	92 ±5	9	20
90 x 9	80	90	-	-	116 ±8	9	20
100 x 9	100	110	100	110	125 ±10	9	20
125 x 9	125	125	125	135	142 ±10	9	20

*Outer diameter in mm (with push-in socket) according to DIN 8062 and DIN EN ISO 1452-2

**Outer diameter in mm according to DIN 19522

