



CLIMAFLEX®

basic
stabil

MATERIAL	CLIMAFLEX® basic stabil is a polyethylene (PE) insulation tube with a co-extruded, tear-resistant outer layer, available in blue or red.
LENGTH	2 m / 10 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C 0,045 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +100 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Heating and plumbing

ADVANTAGES

- Tear-resistant outer layer for protection against mechanical damage during installation and underground installation.
- For insulating cold water and drinking water pipes to reduce heat transfer and condensation formation.

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX®

basic
stabil



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm	A mm	B mm	Pkg unit m
CLIMAFLEX® basic stabil blue 10m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	270
22 x 6	20	22	15	21,3	1/2	20	22	6	250
28 x 6	25	28	20	26,9	3/4	25	28	6	220
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil blue 2 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	440
18 x 6	15	18	10	17,2	3/8	16	18	6	400
22 x 6	20	22	15	21,3	1/2	20	22	6	320
28 x 6	25	28	20	26,9	3/4	25	28	6	250
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil red 10m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	270
22 x 6	20	22	15	21,3	1/2	20	22	6	250
28 x 6	25	28	20	26,9	3/4	25	28	6	220
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil red 2 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	440
18 x 6	15	18	10	17,2	3/8	16	18	6	400
22 x 6	20	22	15	21,3	1/2	20	22	6	320
28 x 6	25	28	20	26,9	3/4	25	28	6	250
35 x 6	32	35	25	33,7	1	32	35	6	180