

CLIMAFLEX® basic stabil

MATERIAL	CLIMAFLEX® basic stabil is a polyethylene (PE) insulation tube with a co-extruded, tear-resistant outer layer, available in blue or red.
LENGTH	2 m / 10 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C 0,045 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +100 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Heating and plumbing

ADVANTAGES


- Tear-resistant outer layer for protection against mechanical damage during installation and underground installation.
- For insulating cold water and drinking water pipes to reduce heat transfer and condensation formation.

See website for Declaration of performance: www.nmc-insulation.com

NMC (UK) LTD.
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

PRODUCT RANGE

CLIMAFLEX® basic stabil



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
CLIMAFLEX® basic stabil blue 10 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	270
22 x 6	20	22	15	21,3	1/2	20	22	6	250
28 x 6	25	28	20	26,9	3/4	25	28	6	220
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil blue 2 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	440
18 x 6	15	18	10	17,2	3/8	16	18	6	400
22 x 6	20	22	15	21,3	1/2	20	22	6	320
28 x 6	25	28	20	26,9	3/4	25	28	6	250
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil red 10 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	270
22 x 6	20	22	15	21,3	1/2	20	22	6	250
28 x 6	25	28	20	26,9	3/4	25	28	6	220
35 x 6	32	35	25	33,7	1	32	35	6	180
CLIMAFLEX® basic stabil red 2 m length									
12/15 x 6	10	12/15	8	13,5	1/4	-	12/15	6	440
18 x 6	15	18	10	17,2	3/8	16	18	6	400
22 x 6	20	22	15	21,3	1/2	20	22	6	320
28 x 6	25	28	20	26,9	3/4	25	28	6	250
35 x 6	32	35	25	33,7	1	32	35	6	180

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com