



CLIMAFLEX®

protect

MATERIAL	CLIMAFLEX® protect is a tube made of closed-cell foam based on polyethylene with a robust outer skin.
LENGTH	10 m
TEMPERATURE RANGE (EN 14707)	Up to +95 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Cold water pipes

ADVANTAGES

- Inner gliding foil for easy pipe covering
- Protection against damage
- Corrosion protection for metal pipes

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX® | protect



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm			
15 x 4	10	15	8	13,5	1/4	-	20 ±2	4	280
18 x 4	15	18	10	17,2	3/8	16	25 ±2	4	240
22 x 4	20	22	15	21,3	1/2	20	27 ±2	4	240
28 x 4	25	28	20	26,9	3/4	25	33 ±2	4	210
35 x 4	32	35	25	33,7	1	32	40 ±2	4	160
42 x 4	40	42	32	42,4	1 1/4	40	45 ±2	4	120

