



CLIMAFLEX®

protect

MATERIAL	CLIMAFLEX® protect is an insulation tube made of closed-cell polyethylene (PE) foam with a robust outer skin.
LENGTH	10 m
TEMPERATURE RANGE (EN 14707)	Up to +95 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Cold water pipes

ADVANTAGES

- Suitable for insulating drinking water and cold-water pipes in accordance with DIN 1988-200, especially for concealed and screed installations requiring enhanced mechanical protection.
- Helps limit condensation formation on cold-carrying metal and plastic pipes.
- Can reduce flow and cracking noises in piping systems.
- The integrated inner sliding film enables quick and easy fitting onto the pipe.

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX®

protect



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm	A mm	B mm	Pkg unit m
15 x 4	10	15	8	13,5	1/4	-	20±2	4	280
18 x 4	15	18	10	17,2	3/8	16	25±2	4	240
22 x 4	20	22	15	21,3	1/2	20	27±2	4	240
28 x 4	25	28	20	26,9	3/4	25	33±2	4	210
35 x 4	32	35	25	33,7	1	32	40±2	4	160
42 x 4	40	42	32	42,4	1 1/4	40	45±2	4	120