



CLIMAFLEX®

protect

MATERIAL	CLIMAFLEX® protect is a tube made of closed-cell foam based on polyethylene with a robust outer skin.
LENGTH	10 m
TEMPERATURE RANGE (EN 14707)	Up to +95 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Cold water pipes
ADVANTAGES	<ul style="list-style-type: none">▪ Inner gliding foil for easy pipe covering▪ Protection against damage▪ Corrosion protection for metal pipes

See website for Declaration of performance: www.nmc-insulation.com



NMC (UK) LTD.

Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277


Email: enquiries@nmc-uk.com

www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX® | protect



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm			
15 x 4	10	15	8	13,5	1/4	-	20±2	4	280
18 x 4	15	18	10	17,2	3/8	16	25±2	4	240
22 x 4	20	22	15	21,3	1/2	20	27±2	4	240
28 x 4	25	28	20	26,9	3/4	25	33±2	4	210
35 x 4	32	35	25	33,7	1	32	40±2	4	160
42 x 4	40	42	32	42,4	1 1/4	40	45±2	4	120

