


# CLIMAFLEX® | protect

| | |
|---|---|
| **MATERIAL** | CLIMAFLEX® protect is an insulation tube made of closed-cell polyethylene (PE) foam with a robust outer skin. |
| **LENGTH** | 10 m |
| **TEMPERATURE RANGE (EN 14707)** | Up to +95 °C |
| **FIRE PERFORMANCE (EN 13501-1)** | Euroclass E |
| **APPLICATION AREA** | Cold water pipes |

**ADVANTAGES**


- Suitable for insulating drinking water and cold-water pipes in accordance with DIN 1988-200, especially for concealed and screed installations requiring enhanced mechanical protection.
- Helps limit condensation formation on cold-carrying metal and plastic pipes.
- Can reduce flow and cracking noises in piping systems.
- The integrated inner sliding film enables quick and easy fitting onto the pipe.

See website for Declaration of performance: www.nmc-insulation.com

**NMC (UK) LTD.**
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

# PRODUCT RANGE

## CLIMAFLEX® | protect




| | Copper CU | | Steel FE | | | Synthetics MSV & PEX | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Type** | **NW DN** | **Outer Ø mm** | **NW DN** | **Outer Ø mm** | **Outer Ø inch** | **Outer Ø mm** | **A mm** | **B mm** | **Pkg unit m** |
| 15 x 4 | 10 | 15 | 8 | 13,5 | 1/4 | - | 20 ±2 | 4 | 280 |
| 18 x 4 | 15 | 18 | 10 | 17,2 | 3/8 | 16 | 25 ±2 | 4 | 240 |
| 22 x 4 | 20 | 22 | 15 | 21,3 | 1/2 | 20 | 27 ±2 | 4 | 240 |
| 28 x 4 | 25 | 28 | 20 | 26,9 | 3/4 | 25 | 33 ±2 | 4 | 210 |
| 35 x 4 | 32 | 35 | 25 | 33,7 | 1 | 32 | 40 ±2 | 4 | 160 |
| 42 x 4 | 40 | 42 | 32 | 42,4 | 1 1/4 | 40 | 45 ±2 | 4 | 120 |



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com