




CLIMAFLEX®

roll

MATERIAL	CLIMAFLEX® ROLL is a flexible insulation made of closed-cell, cross-linked polyethylene foam.
THERMAL CONDUCTIVITY (EN 12667)	0,039 W/mK at 0 °C 0,045 W/mK at 40 °C 0,051 W/mK at 90 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +100 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Heating and plumbing

ADVANTAGES

- Suitable for cutting and fitting complex geometries such as flanges, large-diameter pipes and ventilation ducts in heating and plumbing applications.
- Contributes to the energy-efficient operation of heating and plumbing systems by reducing heat loss.
- The closed-cell material structure can reduce flow and creaking noises, thereby improving acoustic comfort.

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu



PRODUCT RANGE

CLIMAFLEX® | roll



Type	A mm	B mm	Length m	Pkg unit m²
1000 x 10	1000	10	30	30
1000 x 15	1000	15	25	25
1000 x 20	1000	20	25	25