

CLIMAFLEX®

spiral

MATERIAL	CLIMAFLEX® SPIRAL is a ventilation duct made of spiral polyethylen foam. The insulation layer consists of a 16 mm thick PE foam wall of tried and tested NMC quality. A range of different angles and sleeves guarantees that installation can be adapted to the relevant needs.
LENGTH	2 m
INSIDE DIAMETER	125, 150, 160, 180 and 200 mm
WALL THICKNESS	16 mm
THERMAL CONDUCTIVITY (EN ISO 8497)	≤ 0,048 W/mK at 40 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Ventilation

ADVANTAGES	<ul style="list-style-type: none">▪ Alternative to conventional ventilation pipes▪ Simple and quick to fit▪ Elbows available in all diameters, in angels of 30°, 45° and 90°▪ Low weight▪ Non air permeable▪ Corrosion-free▪ Acoustic insulation▪ Not UV-resistant
-------------------	---

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

CLIMAFLEX® | spiral



Type	Thickness	Length	Pkg unit	
	mm	mm	pcs	m
125 x 16	16 ±1	2000 ±30	8	16
150 x 16	16 ±1	2000 ±30	6	12
160 x 16	16 ±1	2000 ±30	6	12
180 x 16	16 ±1	2000 ±30	4	8
200 x 16	16 ±1	2000 ±30	3	6

BOWS

CLIMAFLEX® | spiral

30°



45°



90°



Bow	Pkg unit (pcs)				
	Ø 125	Ø 150	Ø 160	Ø 180	Ø 200
30°	40	30	24	-	-
45°	32	24	20	12	10
90°	20	12	12	8	6

