

Product name: **CLIMAFLEX® naturefoam exzentro**

DoP NR.: W1PEF400

1. Unique identification code of the product-type:

	Unique identification code of the product-type:	W1PEF-004a	W1PEF-004b	
	Thickness:	Inner diameter:	Inner diameter:	
	9 mm	15-35 mm	-	
	25-51 mm	-	15-42 mm	

2. Intended use or uses:

Thermal Insulation for Building Equipment and Industrial Installations (ThIBEII)

3. Manufacturer:

NMC sa, Gert-Noël-Straße, B-4731 Eynatten

5. System or systems of assessment and verification of constancy of performance:

Systems 3

6a. Harmonized standard:

EN 14313:2009+A1:2013

6b. Notified bodies:

NB 1004 IBP / NB 0761 IBMB

7. Declared performance(s):

	Unique identification code of the product-type:	W1PEF-004a	W1PEF-004b	
Requirement/Characteristics from the mandate	Requirement clauses in the european standard	Perfromances: levels of classes	Perfromances: levels of classes	
Reaction to fire Euroclass characterisitcs	4.2.4 Reaction to fire	EI	EI	
Acoustic absorption index	4.3.7 Structure-borne sound transmission	NPD	NPD	
	4.3.8 Sound absoprtion	NPD	NPD	
Thermal resistance	4.2.1 Thermal conductivity	0,036 at 0°C	0,037 at 0°C	
		0,040 at 40°C	0,042 at 40°C	
		0,053 at 90°C	0,055 at 90°C	
	4.2.2 Dimensions of tolerances	See table 1 & 2 point 4.2.2.2. of the standard	See table 1 & 2 point 4.2.2.2. of the standard	
Water permeability	4.3.4 Water absorption	WS005	WS005	
Water vapour permeability	4.3.4 Water absorption	WS005	WS005	
	4.3.5 Water vapour diffusion resistance	NPD	NPD	
Compressive strength		a	a	
Rate of release of corrosive substances	4.3.6 Trace quantities of water-soluble ions & pH-value	NPD	NPD	
Release of dangerous substances to the indoor environment	4.3.9 Release of dangerous substances	b	b	
Continuous glowing combustion	4.3.10 Continuous glowing combustion	b	b	
Durability of reaction to fire against ageing/degradation	4.2.5. Durability characteristics	c	c	
Durability of thermal resistance against ageing/degradation	4.2.1 Thermal conductivity	d	d	
	4.2.2 Dimensions and Tolerances	See table 1 & 2 point 4.2.2.2. of the standard	See table 1 & 2 point 4.2.2.2. of the standard	
	4.2.3 Dimension stability	See 4.3.2	See 4.3.2	
	4.2.5 Durability characteristics	d	d	
	4.3.2 Maximum service temperature	ST (+) 100°C	ST (+) 100°C	
	4.3.3 Minimum service temperature	ST (-) 0°C	ST (-) 0°C	
Durability of reaction to fire against high temperature	4.2.5 Durability characteristics	c	c	
Durability of reaction to fire against high temperature	4.2.5 Durability characteristics	d	d	
	4.3.2 Maximum service temperature – dimentional stability	ST (+) 100°C	ST (+) 100°C	

Note:

NPD: No Performance Determined

a: Compressive strength is not applicable for PEF products

b: At the time of edition of this product standard, no CE test standard is available

c: The fire performance of polyethylene foam does not change with time


d: The thermal conductivity of polyethylene foam does not change with time

The performances of the product identified above is in conformity with the declared performance. In accordance with Regulation (EU) No 305/2011, this declaration of performance is issued under the sole responsibility of the manufacturer.

Digital version of the Declaration of Performance is available on the website www.nmc-insulation.com/download.

Signed for and on behalf of the manufacturer by:

Y. BONNI
Quality Manager

A handwritten signature in dark ink, appearing to read 'Y. BONNI', with a long, sweeping horizontal stroke extending to the right.

Eynatten, x-x-x

Gert-Noël-Straße, B-4731 Eynatten
