

INSUL ROLL

MATERIAL	INSUL ROLL is a flexible insulation material made of black closed-cell synthetic rubber in roll form.
THERMAL CONDUCTIVITY (EN ISO 8497)	0,033 W/mK at - 50 °C 0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	-50 °C to +105 °C
FIRE PERFORMANCE (EN 13501-1)	Bs3d0
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≤ 25 mm: 10.000 μ ≥ 32 mm: 7.000 μ
APPLICATION AREA	Heating and plumbing Cooling systems Air conditioning Shipbuilding


ADVANTAGES

- High thermal insulation performance due to low thermal conductivity, helping to reduce heat loss.
- Reduces condensation build-up and helps protect against moisture-related corrosion.
- Closed-cell material structure with high resistance to water vapour diffusion.
- Sound-insulating properties help reduce flow and operating noise.
- Particularly suitable for custom cutting around large-diameter pipes, HVAC and air ducts, flanges and vessels.

See website for Declaration of performance: www.nmc-insulation.com

NMC (UK) LTD.
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

PRODUCT RANGE
INSUL ROLL



Type	A mm	B mm	Length m	Pkg unit m^2
1000 x 3	1000	3	40	40
1000 x 6	1000	6	20	20
1000 x 9	1000	9	15	15
1000 x 13	1000	13	11	11
1000 x 16	1000	16	9	9
1000 x 19	1000	19	8	8
1000 x 25	1000	25	6	6
1000 x 32	1000	32	4	4
1000 x 40	1000	40	4	4
1000 x 50	1000	50	4	4

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com