



INSUL TAPE

DESCRIPTION	Flexible insulating tape made from synthetic rubber	
DIMENSIONS	3 mm x 50 mm (15 m length)	
THERMAL CONDUCTIVITY (EN ISO 12667)	0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C	
TEMPERATURE RANGE (EN 14707)	-30 °C to +95 °C	
FIRE PERFORMANCE (EN 13501-1)	Bs3d0	
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	10.000 µ	
PROCESSING TEMPERATURE	≥ +5 °C	
APPLICATION AREA	Heating and plumbing Cooling systems	Air conditioning
CHARACTERISTICS	■ Not UV resistant	

See website for Declaration of performance: www.nmc-insulation.com



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher:
NMC sa · Gert-Noël-Strasse · B-4731 Eynatten

NMC sa

Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com

