



INSUL TAPE

BESCHRIJVING	Flexibele isolatietape op basis van synthetisch rubber	
AFMETINGEN	3 mm x 50 mm (15 m lengte)	
THERMISCHE WARMTEGELEIDING (EN ISO 12667)	0,034 W/mK bij -30 °C 0,036 W/mK bij 0 °C 0,039 W/mK bij 40 °C 0,044 W/mK bij 70 °C	
GEbruIKSTEMPERATUUR (EN 14707)	-30 °C tot +95 °C	
BRANDGEDRAG (EN 13501-1)	Bs3d0	
WATERDAMP- DIFFUSIEWEERSTAND (EN 13469)	10.000 µ	
VERWERKINGS- TEMPERATUUR	≥ +5 °C	
TOEPASSINGSGBIED	Verwarming en Sanitair Koelstystemen	Airconditioning
EIGENSCHAPPEN	▪ Niet UV bestendig	

Zie onze website voor Declaration of Performance: www.nmc-insulation.com



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher:
NMC sa · Gert-Noël-Strasse · B-4731 Eynatten

NMC sa

Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com

