

INSUL TAPE

DESCRIPTION	Flexible insulating tape made from synthetic rubber
DIMENSIONS	3 mm x 50 mm (15 m length)
THERMAL CONDUCTIVITY (EN ISO 12667)	0,034 W/mK at -30 °C 0,036 W/mK at 0 °C 0,039 W/mK at 40 °C 0,044 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	-30 °C to +95 °C
FIRE PERFORMANCE (EN 13501-1)	Bs3d0
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	10.000 µ
PROCESSING TEMPERATURE	≥ +5 °C
APPLICATION AREA	Heating and plumbing Air conditioning Cooling systems

CHARACTERISTICS	▪ Not UV resistant

See website for Declaration of performance: www.nmc-insulation.com

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher:
NMC sa · Gert-Noël-Strasse · B-4731 Eynatten

NMC (uk) ltd.
Tafarnaubach Industrial Estate ·
UK - NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com