INSUL-TUBE®

MATERIAL	INSUL-TUBE® jest elastyczna izolacja wykonana z czarnego kauczuku syntetycznego o zamkniętokomórkowej strukturze.	
DLUGOŚĆ	2 m	
PRZEWODNOŚĆ CIEPLNA (EN ISO 8497)	6 - 25 mm 0,033 W/mK at -30 °C 0,034 W/mK at 0 °C 0,038 W/mK at 40 °C 0,041 W/mK at 70 °C	32 - 50 mm 0,031 W/mK at -30 °C 0,035 W/mK at 0 °C 0,040 W/mK at 40 °C 0,043 W/mK at 70 °C
ZAKRES TEMPERATUR (EN 14707)	-30 °C do +110 °C	
ODPORNOŚĆ NA OGIEŃ (EN 13501-1)	B_Ls3d0	
ODPORNOŚĆ NA DYFUZJĘ PARY WODNEJ (EN 13469)	≤ 25 mm: 10.000 μ ≥ 32 mm: 7.000 μ	
OBSZARY ZASTOSOWAŃ	Systemy grzewcze i hydrauliczne Systemy chłodzenia	Klimatyzacja Budowa statków

ZALETY

- Wysoka skuteczność izolacji dzięki niskiemu współczynnikowi przewodzenia cieplnego, który pomaga ograniczyć straty ciepła.
- Ogranicza powstawanie kondensatu i wspomaga ochronę przed korozją powodowaną przez wilgoć.
- Zamkniętokomórkowa struktura materiału o wysokiej odporności na dyfuzję pary wodnej.
- Właściwości dźwiękochłonne pomagają ograniczać hałas przepływu oraz hałas eksploatacyjny.

Deklaracja właściwości użytkowych – zob. strona internetowa: www.nmc-insulation.com

NMC Polska
ul. Pyskowicka 15 · PL-41807 Zabrze
Phone : +48 32 373 24 40 · Fax : +48 32 373 24 43
E-Mail: biuro@nmc.pl
www.nmc-insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
6 x 6	4	6	-	-	-	-	6	6	500
8 x 6	6	8	-	-	-	-	8	6	480
10 x 6	8	10	6	10,2	1/8	-	10	6	430
12 x 6	10	12	-	-	-	-	12	6	350
15 x 6	10	15	8	13,5	1/4	-	15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	280
22 x 6	20	22	15	21,3	1/2	20	22	6	216
28 x 6	25	28	20	26,9	3/4	25	28	6	150
35 x 6	32	35	25	33,7	1	32	35	6	120
6 x 9	4	6	-	-	-	-	6	9	330
8 x 9	6	8	-	-	-	-	8	9	310
10 x 9	8	10	6	10,2	1/8	-	10	9	290
12 x 9	10	12	-	-	-	-	12	9	250
15 x 9	10	15	8	13,5	1/4	-	15	9	212
18 x 9	15	18	10	17,2	3/8	16	18	9	160
22 x 9	20	22	15	21,3	1/2	20	22	9	140
25 x 9	20	25	-	25	3/4	25	25	9	130
28 x 9	25	28	20	26,9	3/4	25	28	9	124
35 x 9	32	35	25	33,7	1	32	35	9	92
42 x 9	40	42	32	42,4	1 1/4	40	42	9	70
48 x 9	-	-	40	48,3	1 1/2	-	48	9	60
54 x 9	50	54	-	54	-	50	54	9	60
60 x 9	-	-	50	60,3	2	-	60	9	60
64 x 9	-	64	-	63,5	-	63	64	9	54
76 x 9	65	76,1	65	76,1	2 1/2	-	76	9	54

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
89 x 9	80	88,9	80	88,9	3	-	89	9	36
102 x 9	-	-	-	101,6	3 1/2	-	102	9	28
108 x 9	100	108	-	108	-	-	108	9	28
114 x 9	100	114	100	114,3	4	-	114	9	28
6 x 13	4	6	-	-	-	-	6	13	240
10 x 13	8	10	6	10,2	1/8	-	10	13	190
12 x 13	10	12	-	-	-	-	12	13	172
15 x 13	10	15	8	13,5	1/4	-	15	13	140
18 x 13	15	18	10	17,2	3/8	16	18	13	130
20 x 13	15	19	-	-	1/2	20	20	13	110
22 x 13	20	22	15	21,3	1/2	20	22	13	98
25 x 13	20	25	-	25	3/4	25	25	13	92
28 x 13	25	28	20	26,9	3/4	25	28	13	86
32 x 13	-	-	-	-	1	32	32	13	76
35 x 13	32	35	25	33,7	1	32	35	13	76
40 x 13	-	-	-	-	-	-	40	13	56
42 x 13	40	42	32	42,4	1 1/4	40	42	13	56
48 x 13	-	-	40	48,3	1 1/2	-	48	13	48
50 x 13	-	-	-	-	-	-	50	13	46
54 x 13	50	54	-	54	-	50	54	13	46
60 x 13	-	-	50	60,3	2	-	60	13	40
64 x 13	-	64	-	63,5	-	63	64	13	40
67 x 13	-	-	-	-	-	-	67	13	40
76 x 13	65	76,1	65	76,1	2 1/2	-	76	13	34
80 x 13	-	80	-	-	-	-	80	13	30

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
89 x 13	80	88,9	80	88,9	3	-	89	13	30
102 x 13	-	-	-	101,6	3 1/2	-	102	13	30
108 x 13	100	108	-	108	-	-	108	13	28
114 x 13	100	114	100	114,3	4	-	114	13	28
125 x 13	-	-	-	125	-	-	125	13	20
133 x 13	125	133	125	133	-	-	133	13	18
160 x 13	150	159	-	160	-	-	160	13	16
10 x 19	8	10	6	10,2	1/8	-	10	19	106
12 x 19	10	12	-	-	-	-	12	19	100
15 x 19	10	15	8	13,5	1/4	-	15	19	86
18 x 19	15	18	10	17,2	3/8	16	18	19	78
20 x 19	15	19	-	-	1/2	20	20	19	76
22 x 19	20	22	15	21,3	1/2	20	22	19	74
25 x 19	20	25	-	25	3/4	25	25	19	60m
28 x 19	25	28	20	26,9	3/4	25	28	19	58
32 x 19	-	-	-	-	1	32	32	19	54
35 x 19	32	35	25	33,7	1	32	35	19	48
40 x 19	-	-	-	-	-	-	40	19	40
42 x 19	40	42	32	42,4	1 1/4	40	42	19	40
48 x 19	-	-	40	48,3	1 1/2	-	48	19	30
50 x 19	-	-	-	-	-	-	50	19	30
54 x 19	50	54	-	54	-	50	54	19	30
60 x 19	-	-	50	60,3	2	-	60	19	28
64 x 19	-	64	-	63,5	-	63	64	19	28
67 x 19	-	-	-	-	-	-	67	19	28

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
76 x 19	65	76,1	65	76,1	2 1/2	-	76	19	28
80 x 19	-	80	-	-	-	-	80	19	26
89 x 19	80	88,9	80	88,9	3	-	89	19	22
102 x 19	-	-	-	101,6	3 1/2	-	102	19	20
108 x 19	100	108	-	108	-	-	108	19	20
114 x 19	100	114	100	114,3	4	-	114	19	18
125 x 19	-	-	-	125	-	-	125	19	18
133 x 19	125	133	125	133	-	-	133	19	12
140 x 19	-	-	125	139,7	5	-	140	19	10
160 x 19	150	159	-	160	-	-	160	19	8
10 x 25	8	10	6	10,2	1/8	-	10	25	60
12 x 25	10	12	-	-	-	-	12	25	50
15 x 25	10	15	8	13,5	1/4	-	15	25	50
18 x 25	15	18	10	17,2	3/8	16	18	25	50
20 x 25	15	19	-	-	1/2	20	20	25	50
22 x 25	20	22	15	21,3	1/2	20	22	25	42
25 x 25	20	25	-	25	3/4	25	25	25	40
28 x 25	25	28	20	26,9	3/4	25	28	25	40
32 x 25	-	-	-	-	1	32	32	25	36
35 x 25	32	35	25	33,7	1	32	35	25	32
42 x 25	40	42	32	42,4	1 1/4	40	42	25	24
48 x 25	-	-	40	48,3	1 1/2	-	48	25	24
54 x 25	50	54	-	54	-	50	54	25	22
60 x 25	-	-	50	60,3	2	-	60	25	22
64 x 25	-	64	-	63,5	-	63	64	25	18

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
67 x 25	-	-	-	-	-	-	67	25	18
70 x 25	-	70	-	70	-	-	70	25	18
76 x 25	65	76,1	65	76,1	2 1/2	-	76	25	18
89 x 25	80	88,9	80	88,9	3	-	89	25	14
102 x 25	-	-	-	101,6	3 1/2	-	102	25	12
108 x 25	100	108	100	108	-	-	108	25	10
114 x 25	100	114	100	114,3	4	-	114	25	10
125 x 25	-	-	-	125	-	-	125	25	8
133 x 25	125	133	125	133	-	-	133	25	8
140 x 25	-	-	125	139,7	5	-	140	25	6
160 x 25	150	159	-	160	-	-	160	25	4
12 x 32	10	12	-	-	-	-	12	32	36
15 x 32	10	15	8	13,5	1/4	-	15	32	32
18 x 32	15	18	10	17,2	3/8	16	18	32	32
22 x 32	20	22	15	21,3	1/2	20	22	32	26
28 x 32	25	28	20	26,9	3/4	25	28	32	24
32 x 32	-	-	-	-	1	32	32	32	24
35 x 32	32	35	25	33,7	1	32	35	32	24
42 x 32	40	42	32	42,4	1 1/4	40	42	32	18
48 x 32	-	-	40	48,3	1 1/2	-	48	32	18
54 x 32	50	54	-	54	-	50	54	32	16
60 x 32	-	-	50	60,3	2	-	60	32	16
64 x 32	-	63	-	63,5	-	63	64	32	14
67 x 32	-	-	-	-	-	-	67	32	14
70 x 32	-	70	-	70	-	-	70	32	14

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
76 x 32	65	76,1	65	76,1	2 1/2	-	76	32	12
80 x 32	-	80	-	-	-	-	80	32	12
89 x 32	80	88,9	80	88,9	3	-	89	32	10
102 x 32	-	-	-	101,6	3 1/2	-	102	32	10
108 x 32	100	108	-	108	-	-	108	32	8
114 x 32	100	114	100	114,3	4	-	114	32	8
125 x 32	-	-	-	125	-	-	125	32	6
133 x 32	125	133	125	133	-	-	133	32	6
140 x 32	-	-	125	139,7	5	-	140	32	6
160 x 32	150	159	-	160	-	-	160	32	4
18 x 40	15	18	10	17,2	3/8	16	18	40	22
22 x 40	20	22	15	21,3	1/2	20	22	40	22
28 x 40	25	28	20	26,9	3/4	25	28	40	16
32 x 40	-	-	-	-	1	32	32	40	16
35 x 40	32	35	25	33,7	1	32	35	40	12
42 x 40	40	42	32	42,4	1 1/4	40	42	40	12
48 x 40	-	-	40	48,3	1 1/2	-	48	40	12
54 x 40	50	54	-	54	-	50	54	40	10
60 x 40	-	-	50	60,3	2	-	60	40	10
64 x 40	-	63	-	63,5	-	63	64	40	10
70 x 40	-	70	-	70	-	-	70	40	10
76 x 40	65	76,1	65	76,1	2 1/2	-	76	40	10
80 x 40							80	40	10
89 x 40	80	88,9	80	88,9	3	-	89	40	8
102 x 40	-	-	-	101,6	3 1/2	-	102	40	6

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

ASORTYMENT
INSUL-TUBE®



	Miedź CU		Stal FE			Tworzywo szluczne			
Type	NW	Ø zewnerzna	NW	Ø zewnerzna		Ø zewnerzna	A	B	m/karton
	DN	mm	DN	mm	inch	mm	mm	mm	m
108 x 40	100	108	-	108	-	-	108	40	6
114 x 40	100	114	100	114,3	4	-	114	40	4
125 x 40	-	-	-	125	-	-	125	40	4
140 x 40	-	-	125	139,7	5	-	140	40	4
160 x 40	150	159	-	160	-	-	160	40	4
35 x 50	32	35	25	33,7	1	32	35	50	8
42 x 50	40	42	32	42,4	1 1/4	40	42	50	8
48 x 50	-	-	40	48,3	1 1/2	-	48	50	8
54 x 50	50	54	-	54	-	50	54	50	8
60 x 50	-	-	50	60,3	2	-	60	50	8
64 x 50	-	63	-	63,5	-	63	64	50	8
76 x 50	65	76,1	65	76,1	2 1/2	-	76	50	6
89 x 50	80	88,9	80	88,9	3	-	89	50	6
114 x 50	100	114	100	114,3	4	-	114	50	4
125 x 50	-	-	-	125	-	-	125	50	4

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.
07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com