

INSUL-TUBE®

MATERIAL	INSUL-TUBE® is a flexible insulation made of black closed-cell synthetic rubber.	
LENGTH	2 m	
THERMAL CONDUCTIVITY (EN ISO 8497)	6 - 25 mm 0,033 W/mK at -30 °C 0,034 W/mK at 0 °C 0,038 W/mK at 40 °C 0,041 W/mK at 70 °C	32 - 50 mm 0,031 W/mK at -30 °C 0,035 W/mK at 0 °C 0,040 W/mK at 40 °C 0,043 W/mK at 70 °C
TEMPERATURE RANGE (EN 14707)	-30 °C to +110 °C	
FIRE PERFORMANCE (EN 13501-1)	B_Ls3d0	
WATER VAPOUR DIFFUSION RESISTANCE (EN 13469)	≤ 25 mm: 10.000 µ ≥ 32 mm: 7.000 µ	
APPLICATION AREA	Heating and plumbing Cooling systems	Air conditioning Ship approval

ADVANTAGES


- High thermal insulation performance due to low thermal conductivity, helping to reduce heat loss.
- Reduces condensation build-up and helps protect against moisture-related corrosion.
- Closed-cell material structure with high resistance to water vapour diffusion.
- Sound-insulating properties help reduce flow and operating noise.

See website for Declaration of performance: www.nmc-insulation.com

NMC (UK) LTD.
Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
Phone: +44 1495 713266 · Fax: +44 1495 713277
Email: enquiries@nmc-uk.com
www.nmc-insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
6 x 6	4	6	-	-	-	-	6	6	500
8 x 6	6	8	-	-	-	-	8	6	480
10 x 6	8	10	6	10,2	1/8	-	10	6	430
12 x 6	10	12	-	-	-	-	12	6	350
15 x 6	10	15	8	13,5	1/4	-	15	6	300
18 x 6	15	18	10	17,2	3/8	16	18	6	280
22 x 6	20	22	15	21,3	1/2	20	22	6	216
28 x 6	25	28	20	26,9	3/4	25	28	6	150
35 x 6	32	35	25	33,7	1	32	35	6	120
6 x 9	4	6	-	-	-	-	6	9	330
8 x 9	6	8	-	-	-	-	8	9	310
10 x 9	8	10	6	10,2	1/8	-	10	9	290
12 x 9	10	12	-	-	-	-	12	9	250
15 x 9	10	15	8	13,5	1/4	-	15	9	212
18 x 9	15	18	10	17,2	3/8	16	18	9	160
22 x 9	20	22	15	21,3	1/2	20	22	9	140
25 x 9	20	25	-	25	3/4	25	25	9	130
28 x 9	25	28	20	26,9	3/4	25	28	9	124
35 x 9	32	35	25	33,7	1	32	35	9	92
42 x 9	40	42	32	42,4	1 1/4	40	42	9	70
48 x 9	-	-	40	48,3	1 1/2	-	48	9	60
54 x 9	50	54	-	54	-	50	54	9	60
60 x 9	-	-	50	60,3	2	-	60	9	60
64 x 9	-	64	-	63,5	-	63	64	9	54
76 x 9	65	76,1	65	76,1	2 1/2	-	76	9	54

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
89 x 9	80	88,9	80	88,9	3	-	89	9	36
102 x 9	-	-	-	101,6	3 1/2	-	102	9	28
108 x 9	100	108	-	108	-	-	108	9	28
114 x 9	100	114	100	114,3	4	-	114	9	28
6 x 13	4	6	-	-	-	-	6	13	240
10 x 13	8	10	6	10,2	1/8	-	10	13	190
12 x 13	10	12	-	-	-	-	12	13	172
15 x 13	10	15	8	13,5	1/4	-	15	13	140
18 x 13	15	18	10	17,2	3/8	16	18	13	130
20 x 13	15	19	-	-	1/2	20	20	13	110
22 x 13	20	22	15	21,3	1/2	20	22	13	98
25 x 13	20	25	-	25	3/4	25	25	13	92
28 x 13	25	28	20	26,9	3/4	25	28	13	86
32 x 13	-	-	-	-	1	32	32	13	76
35 x 13	32	35	25	33,7	1	32	35	13	76
40 x 13	-	-	-	-	-	-	40	13	56
42 x 13	40	42	32	42,4	1 1/4	40	42	13	56
48 x 13	-	-	40	48,3	1 1/2	-	48	13	48
50 x 13	-	-	-	-	-	-	50	13	46
54 x 13	50	54	-	54	-	50	54	13	46
60 x 13	-	-	50	60,3	2	-	60	13	40
64 x 13	-	64	-	63,5	-	63	64	13	40
67 x 13	-	-	-	-	-	-	67	13	40
76 x 13	65	76,1	65	76,1	2 1/2	-	76	13	34
80 x 13	-	80	-	-	-	-	80	13	30

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
89 x 13	80	88,9	80	88,9	3	-	89	13	30
102 x 13	-	-	-	101,6	3 1/2	-	102	13	30
108 x 13	100	108	-	108	-	-	108	13	28
114 x 13	100	114	100	114,3	4	-	114	13	28
125 x 13	-	-	-	125	-	-	125	13	20
133 x 13	125	133	125	133	-	-	133	13	18
160 x 13	150	159	-	160	-	-	160	13	16
10 x 19	8	10	6	10,2	1/8	-	10	19	106
12 x 19	10	12	-	-	-	-	12	19	100
15 x 19	10	15	8	13,5	1/4	-	15	19	86
18 x 19	15	18	10	17,2	3/8	16	18	19	78
20 x 19	15	19	-	-	1/2	20	20	19	76
22 x 19	20	22	15	21,3	1/2	20	22	19	74
25 x 19	20	25	-	25	3/4	25	25	19	60m
28 x 19	25	28	20	26,9	3/4	25	28	19	58
32 x 19	-	-	-	-	1	32	32	19	54
35 x 19	32	35	25	33,7	1	32	35	19	48
40 x 19	-	-	-	-	-	-	40	19	40
42 x 19	40	42	32	42,4	1 1/4	40	42	19	40
48 x 19	-	-	40	48,3	1 1/2	-	48	19	30
50 x 19	-	-	-	-	-	-	50	19	30
54 x 19	50	54	-	54	-	50	54	19	30
60 x 19	-	-	50	60,3	2	-	60	19	28
64 x 19	-	64	-	63,5	-	63	64	19	28
67 x 19	-	-	-	-	-	-	67	19	28

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
76 x 19	65	76,1	65	76,1	2 1/2	-	76	19	28
80 x 19	-	80	-	-	-	-	80	19	26
89 x 19	80	88,9	80	88,9	3	-	89	19	22
102 x 19	-	-	-	101,6	3 1/2	-	102	19	20
108 x 19	100	108	-	108	-	-	108	19	20
114 x 19	100	114	100	114,3	4	-	114	19	18
125 x 19	-	-	-	125	-	-	125	19	18
133 x 19	125	133	125	133	-	-	133	19	12
140 x 19	-	-	125	139,7	5	-	140	19	10
160 x 19	150	159	-	160	-	-	160	19	8
10 x 25	8	10	6	10,2	1/8	-	10	25	60
12 x 25	10	12	-	-	-	-	12	25	50
15 x 25	10	15	8	13,5	1/4	-	15	25	50
18 x 25	15	18	10	17,2	3/8	16	18	25	50
20 x 25	15	19	-	-	1/2	20	20	25	50
22 x 25	20	22	15	21,3	1/2	20	22	25	42
25 x 25	20	25	-	25	3/4	25	25	25	40
28 x 25	25	28	20	26,9	3/4	25	28	25	40
32 x 25	-	-	-	-	1	32	32	25	36
35 x 25	32	35	25	33,7	1	32	35	25	32
42 x 25	40	42	32	42,4	1 1/4	40	42	25	24
48 x 25	-	-	40	48,3	1 1/2	-	48	25	24
54 x 25	50	54	-	54	-	50	54	25	22
60 x 25	-	-	50	60,3	2	-	60	25	22
64 x 25	-	64	-	63,5	-	63	64	25	18

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
67 x 25	-	-	-	-	-	-	67	25	18
70 x 25	-	70	-	70	-	-	70	25	18
76 x 25	65	76,1	65	76,1	2 1/2	-	76	25	18
89 x 25	80	88,9	80	88,9	3	-	89	25	14
102 x 25	-	-	-	101,6	3 1/2	-	102	25	12
108 x 25	100	108	100	108	-	-	108	25	10
114 x 25	100	114	100	114,3	4	-	114	25	10
125 x 25	-	-	-	125	-	-	125	25	8
133 x 25	125	133	125	133	-	-	133	25	8
140 x 25	-	-	125	139,7	5	-	140	25	6
160 x 25	150	159	-	160	-	-	160	25	4
12 x 32	10	12	-	-	-	-	12	32	36
15 x 32	10	15	8	13,5	1/4	-	15	32	32
18 x 32	15	18	10	17,2	3/8	16	18	32	32
22 x 32	20	22	15	21,3	1/2	20	22	32	26
28 x 32	25	28	20	26,9	3/4	25	28	32	24
32 x 32	-	-	-	-	1	32	32	32	24
35 x 32	32	35	25	33,7	1	32	35	32	24
42 x 32	40	42	32	42,4	1 1/4	40	42	32	18
48 x 32	-	-	40	48,3	1 1/2	-	48	32	18
54 x 32	50	54	-	54	-	50	54	32	16
60 x 32	-	-	50	60,3	2	-	60	32	16
64 x 32	-	63	-	63,5	-	63	64	32	14
67 x 32	-	-	-	-	-	-	67	32	14
70 x 32	-	70	-	70	-	-	70	32	14

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®




	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
76 x 32	65	76,1	65	76,1	2 1/2	-	76	32	12
80 x 32	-	80	-	-	-	-	80	32	12
89 x 32	80	88,9	80	88,9	3	-	89	32	10
102 x 32	-	-	-	101,6	3 1/2	-	102	32	10
108 x 32	100	108	-	108	-	-	108	32	8
114 x 32	100	114	100	114,3	4	-	114	32	8
125 x 32	-	-	-	125	-	-	125	32	6
133 x 32	125	133	125	133	-	-	133	32	6
140 x 32	-	-	125	139,7	5	-	140	32	6
160 x 32	150	159	-	160	-	-	160	32	4
18 x 40	15	18	10	17,2	3/8	16	18	40	22
22 x 40	20	22	15	21,3	1/2	20	22	40	22
28 x 40	25	28	20	26,9	3/4	25	28	40	16
32 x 40	-	-	-	-	1	32	32	40	16
35 x 40	32	35	25	33,7	1	32	35	40	12
42 x 40	40	42	32	42,4	1 1/4	40	42	40	12
48 x 40	-	-	40	48,3	1 1/2	-	48	40	12
54 x 40	50	54	-	54	-	50	54	40	10
60 x 40	-	-	50	60,3	2	-	60	40	10
64 x 40	-	63	-	63,5	-	63	64	40	10
70 x 40	-	70	-	70	-	-	70	40	10
76 x 40	65	76,1	65	76,1	2 1/2	-	76	40	10
80 x 40							80	40	10
89 x 40	80	88,9	80	88,9	3	-	89	40	8
102 x 40	-	-	-	101,6	3 1/2	-	102	40	6

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com

PRODUCT RANGE

INSUL-TUBE®



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm	Outer Ø inch	Outer Ø mm	A mm	B mm	Pkg unit m
108 x 40	100	108	-	108	-	-	108	40	6
114 x 40	100	114	100	114,3	4	-	114	40	4
125 x 40	-	-	-	125	-	-	125	40	4
140 x 40	-	-	125	139,7	5	-	140	40	4
160 x 40	150	159	-	160	-	-	160	40	4
35 x 50	32	35	25	33,7	1	32	35	50	8
42 x 50	40	42	32	42,4	1 1/4	40	42	50	8
48 x 50	-	-	40	48,3	1 1/2	-	48	50	8
54 x 50	50	54	-	54	-	50	54	50	8
60 x 50	-	-	50	60,3	2	-	60	50	8
64 x 50	-	63	-	63,5	-	63	64	50	8
76 x 50	65	76,1	65	76,1	2 1/2	-	76	50	6
89 x 50	80	88,9	80	88,9	3	-	89	50	6
114 x 50	100	114	100	114,3	4	-	114	50	4
125 x 50	-	-	-	125	-	-	125	50	4

NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

07/2026 responsible publisher: NMC sa · Gert - Noël - Strasse · B - 4731 Eynatten · www.nmc - insulation.com