



INSULATION TAPE PE

Flexible polyethylene tape for the use in heating and plumbing

SUPPORT TYPE	Polyethylene foam	
THICKNESS	3 mm	
ROLL WIDTH	50 mm	
ROLL LENGHT	10 m	
COLOR	Grey	
ADHESIVE COMPOSITION	Acrylate dispersion	
LINER	Brown silicone paper	
PEEL ADHESION	DIN EN 1939	Material break
TEMPERATURE RANGE	EN 14707	-30 °C to +100 °C
TENSILE STRENGTH	ISO 1926	Lengthwise: 290 kPa Crosswise: 180 kPa
ELONGATION AT BREAK	ISO 1926	Lengthwise: 130 % Crosswise: 95 %
COMPRESSIVE STRENGTH	ISO 3386-1	110 kPa at 50 % compression
COMPRESSION SET	ISO 1856-C	25 % (22 h at 23 °C) 21 % (0,5 h after discharge) 10 % (24 h after discharge)
WATER ABSORPTION	ISO 2896	< 1 Vol. - % (7d)



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher:
NMC sa · Gert-Noël-Strasse · B-4731 Eynatten

NMC sa

Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com

