



INSULATION TAPE PE

Flexibles Polyethylenband für den Heizungs- und Sanitärbereich

TRÄGERTYP	Polyethylen-Schaum	
DICKE	3 mm	
ROLLENBREITE	50 mm	
ROLLENLÄNGE	10 m	
FARBE	Grau	
KLEBSTOFFBASIS	Acrylat-Dispersion	
ABDECKMATERIAL	Silikonpapier, Braun	
KLEBKRAFT	DIN EN 1939	Materialbruch
TEMPERATURBEREICH	EN 14707	-30 °C bis +100 °C
ZUGFESTIGKEIT	ISO 1926	längs: 290 kPa quer: 180 kPa
BRUCHDEHNUNG	ISO 1926	längs: 130 % quer: 95 %
STAUCHHÄRTE	ISO 3386-1	110 kPa bei 50 % Stauchung
DRUCK- VERFORMUNGSREST	ISO 1856-C	25 % (22 h bei 23 °C) 21 % (0,5 h nach Entlastung) 10 % (24 h nach Entlastung)
WASSERAUFNAHME	ISO 2896	< 1 Vol. - % (7d)



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology anytime and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.

08/2026 responsible publisher:
NMC sa · Gert-Noël-Strasse · B-4731 Eynatten

NMC Deutschland GmbH
Weiherhausstrasse 8b · D-64646 Heppenheim
Tel.: +49 6252 967 0
E-Mail: info@nmc-deutschland.de
www.nmc-insulation.com

