



ISOTUBE®

MATERIAL	ISOTUBE® is a PU foam pipe insulation with PVC jacketing and a self-adhesive closure system.
LENGTH	1 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,032 W/mK at 10 °C 0,036 W/mK at 40 °C 0,038 W/mK at 50 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +140 °C
FIRE PERFORMANCE (EN 13501-1)	E ₁ ,d0
APPLICATION AREA	Heating and plumbing

ADVANTAGES

- High insulation performance due to low thermal conductivity, helping to reduce heat loss.
- Robust factory-applied PVC protective jacketing for increased durability and an attractive appearance.
- Prefabricated 90° system elbows for fast and clean installation of pipe bends without mitre cuts.
- Self-adhesive closure system for quick, easy and secure installation, even on existing pipework.

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

ISOTUBE®



	Copper CU		Steel FE			Synthetics MSV & PEX			
Type	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm	A mm	B mm	Pkg unit m
15 x 20	10	15	8	13,5	1/4	-	15	20	70
18 x 20	15	18	10	17,2	3/8	16	18	20	70
22 x 20	20	22	15	21,3	1/2	20	22	20	60
28 x 20	25	28	20	26,9	3/4	25	28	20	48
35 x 20	32	35	25	33,7	1	32	35	20	40
28 x 30	25	28	20	26,9	3/4	25	28	31	28
35 x 30	32	35	25	33,7	1	32	35	30	24
42 x 40	40	42	32	42,4	1 1/4	40	42	40	15
48 x 40	-	-	40	48,3	1 1/2	-	48	41	12
60 x 50	-	-	50	60,3	2	-	60	49	7