



ISOTUBE®

MATERIAL	ISOTUBE® is a PU foam insulation material protected by a special PVC sheet with a superior appearance.
LENGTH	1 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,032 W/mK at 10 °C 0,036 W/mK at 40 °C 0,038 W/mK at 50 °C
TEMPERATURE RANGE (EN 14707)	0 °C to +140 °C
FIRE PERFORMANCE (EN 13501-1)	E _i ,d0
APPLICATION AREA	Heating and plumbing

ADVANTAGES	<ul style="list-style-type: none"> ▪ Professional thermal insulation for energy savings of up to 80 % ▪ Improvement of the economic and ecological efficiency of the entire unit ▪ High-quality appearance ▪ We offer appropriate elbow joints for every diameter ▪ Protects the foam against any damage ▪ Easy to install
-------------------	--

See website for Declaration of performance: www.nmc-insulation.com




NMC (UK) LTD.
 Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales
 Phone: +44 1495 713266 · Fax: +44 1495 713277
 Email: enquiries@nmc-uk.com
www.nmc-insulation.com



PRODUCT RANGE

ISOTUBE®



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm			
15 x 20	10	15	8	13,5	1/4	-	15	20	70
18 x 20	15	18	10	17,2	3/8	16	18	20	70
22 x 20	20	22	15	21,3	1/2	20	22	20	60
28 x 20	25	28	20	26,9	3/4	25	28	20	48
35 x 20	32	35	25	33,7	1	32	35	20	40
28 x 30	25	28	20	26,9	3/4	25	28	31	28
35 x 30	32	35	25	33,7	1	32	35	30	24
42 x 40	40	42	32	42,4	1 1/4	40	42	40	15
48 x 40	-	-	40	48,3	1 1/2	-	48	41	12
60 x 50	-	-	50	60,3	2	-	60	49	7