



AEROLINE®

inox pro gs

SHEATHING

| | |
|------------------|-----------------|
| MATERIAL | Polyester braid |
| UV RESISTANCE | Excellent |
| OZONE RESISTANCE | Excellent |

STAINLESS STEEL CORRUGATED PIPE

| | |
|---|---------------------------------|
| MATERIAL | Material No. 1.4404 (AISI 316L) |
| MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C | DN 25: 12 bar DN 32: 6,5 bar |

SENSOR CABLE

| | |
|-------------------|--|
| inox pro gs DN 32 | 2 x 0,75 mm ² VDE 7507 |
| inox pro gs DN 25 | 3 x 0,75 mm ² VDE 0295, Silicone, Class 5 |

INSULATION MADE OF EPDM

| | |
|----------------------|---|
| MATERIAL | Light, flexible, closed-cell, synthetic rubber No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304 |
| THERMAL CONDUCTIVITY | 0,036 W/mK at 0 °C 0,038 W/mK at 40 °C |
| FIRE BEHAVIOUR | Euro class E (DIN EN 13501-1) |



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox pro gs

| Reference | SAP | Length (m) |
|--------------|---------|------------|
| DN 25 | | |
| 25 x 25/10 m | 3032769 | 10 |
| 25 x 25/15 m | 3032770 | 15 |
| 25 x 25/20 m | 3032771 | 20 |
| 25 x 25/25 m | 3032772 | 25 |
| 25 x 25/50 m | 3032773 | 50 |
| DN 32 | | |
| 32 x 25/10 m | 3032774 | 10 |
| 32 x 25/15 m | 3032776 | 15 |
| 32 x 25/20 m | 3032777 | 20 |
| 32 x 25/25 m | 3032778 | 25 |