



# AEROFLEX®

sh coil

<b>MATERIAL</b>	AEROFLEX® sh is a flexible, closed-cell insulation based on EPDM.
<b>LENGTH</b>	16 to 30 m
<b>THERMAL CONDUCTIVITY (EN ISO 8497)</b>	0,035 W/mK at 10 °C 0,038 W/mK at 40 °C
<b>TEMPERATURE RANGE (EN 14707)</b>	Up to 110 °C
<b>FIRE PERFORMANCE (EN 13501-1)</b>	C <sub>s</sub> 2d0
<b>APPLICATION AREA</b>	Heating and plumbing
<b>ADVANTAGES</b>	<ul style="list-style-type: none"><li>▪ Limited smoke gas development</li><li>▪ Fulfils the stricter requirements for flame-retardant products in accordance with MVV TB</li><li>▪ Improvement of the economic and ecological efficiency of the entire system</li><li>▪ Sound-absorbing insulation for acoustic comfort</li><li>▪ Minimal cutting scrap</li><li>▪ Minimal edge fittings</li></ul>

See website for Declaration of performance: [www.nmc-insulation.com](http://www.nmc-insulation.com)




**NMC sa**  
Gert-Noël-Strasse · B-4731 Eynatten  
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55  
E-Mail: [info@nmc.eu](mailto:info@nmc.eu)  
[www.nmc-insulation.com](http://www.nmc-insulation.com)



# PRODUCT RANGE

## AEROFLEX® | sh coil



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW DN	Outer Ø mm	NW DN	Outer Ø mm    inch		Outer Ø mm			
15 x 10	10	15	8	13,5	1/4	-	15	12	30
18 x 10	15	18	10	17,2	3/8	16	18	12	30
22 x 10	20	22	15	21,3	1/2	20	22	12	22
28 x 10	25	28	20	26,9	3/4	25	28	12	16