



AEROFLEX®

sh xt

MATERIAL	AEROFLEX® sh is a flexible, closed-cell insulation based on EPDM, equipped with a self-adhesive double-sided closing system.
LENGTH	2 m
THERMAL CONDUCTIVITY (EN ISO 8497)	0,035 W/mK at 10 °C 0,038 W/mK at 40 °C
TEMPERATURE RANGE (EN 14707)	Up to 85 °C
FIRE PERFORMANCE (EN 13501-1)	Euroclass E
APPLICATION AREA	Heating and plumbing
ADVANTAGES	<ul style="list-style-type: none">▪ Limited smoke gas development▪ Fulfils the stricter requirements for flame-retardant products in accordance with MVV TB▪ Improvement of the economic and ecological efficiency of the entire system▪ Sound-absorbing insulation for acoustic comfort▪ Equipped with self-adhesive, double-sided closing system

See website for Declaration of performance: www.nmc-insulation.com




NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Phone: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROFLEX®

sh xt



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A mm	B mm	Pkg unit m
	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch		Outer Ø mm			
15 x 10	10	15	8	13,5	1/4	-	15	12	100
18 x 10	15	18	10	17,2	3/8	16	18	12	80
22 x 10	20	22	15	21,3	1/2	20	22	12	64
28 x 10	25	28	20	26,9	3/4	25	28	12	56
35 x 10	32	35	25	33,7	1	32	35	12	40
42 x 10	40	42	32	42,4	1 1/4	40	42	12	36
48 x 10	-	-	40	48,3	1 1/2	40,2	48	13	32
54 x 10	50	54	-	54	-	50	54	13	28
60 x 10	-	-	50	60,3	2	-	60	13	24
28 x 15	25	28	20	26,9	3/4	25	28	17	36
35 x 15	32	35	25	33,7	1	32	35	17	32