



# CLIMAFLEX®

basic  
stabil

<b>MATERIAL</b>	CLIMAFLEX® basic stabil is a flexible insulating material made of foamed, closed-cell polyethylene with a protective skin.
<b>LENGTH</b>	2 m / 10 m
<b>THERMAL CONDUCTIVITY (EN ISO 8497)</b>	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C 0,045 W/mK at 70 °C
<b>TEMPERATURE RANGE (EN 14707)</b>	0 °C to +100 °C
<b>FIRE PERFORMANCE (EN 13501-1)</b>	Euroclass E
<b>APPLICATION AREA</b>	Heating and plumbing

## ADVANTAGES

- Damage protection
- Energy efficiency
- Protection against condensation and corrosion

See website for Declaration of performance: [www.nmc-insulation.com](http://www.nmc-insulation.com)



### NMC (UK) LTD.

Tafarnaubach Industrial Estate · UK-NP22 3AA Tredegar, South Wales

Phone: +44 1495 713266 · Fax: +44 1495 713277

Email: [enquiries@nmc-uk.com](mailto:enquiries@nmc-uk.com)

[www.nmc-insulation.com](http://www.nmc-insulation.com)



# PRODUCT RANGE

CLIMAFLEX® | basic stabil



Type	Copper CU		Steel FE			Synthetics MSV & PEX	A	B	Pkg unit
	NW DN	Outer Ø mm	NW DN	Outer Ø mm inch	Outer Ø mm	mm			
<b>CLIMAFLEX® basic stabil blue 10 m length</b>									
12/15 x 6	10	12/15	8	13,5 1/4	-	12/15	6	300	
18 x 6	15	18	10	17,2 3/8	16	18	6	270	
22 x 6	20	22	15	21,3 1/2	20	22	6	250	
28 x 6	25	28	20	26,9 3/4	25	28	6	220	
35 x 6	32	35	25	33,7 1	32	35	6	180	
<b>CLIMAFLEX® basic stabil blue 2 m length</b>									
12/15 x 6	10	12/15	8	13,5 1/4	-	12/15	6	440	
18 x 6	15	18	10	17,2 3/8	16	18	6	400	
22 x 6	20	22	15	21,3 1/2	20	22	6	320	
28 x 6	25	28	20	26,9 3/4	25	28	6	250	
35 x 6	32	35	25	33,7 1	32	35	6	180	
<b>CLIMAFLEX® basic stabil red 10 m length</b>									
12/15 x 6	10	12/15	8	13,5 1/4	-	12/15	6	300	
18 x 6	15	18	10	17,2 3/8	16	18	6	270	
22 x 6	20	22	15	21,3 1/2	20	22	6	250	
28 x 6	25	28	20	26,9 3/4	25	28	6	220	
35 x 6	32	35	25	33,7 1	32	35	6	180	
<b>CLIMAFLEX® basic stabil red 2 m length</b>									
12/15 x 6	10	12/15	8	13,5 1/4	-	12/15	6	440	
18 x 6	15	18	10	17,2 3/8	16	18	6	400	
22 x 6	20	22	15	21,3 1/2	20	22	6	320	
28 x 6	25	28	20	26,9 3/4	25	28	6	250	
35 x 6	32	35	25	33,7 1	32	35	6	180	