



AEROLINE®

inox rapid pro

SHEATHING

| | |
|----------|--|
| MATERIAL | Mounting protection made from strong polyester fabric / stainless steel wire |
| | Very good ozone resistance, UV-resistant |

STAINLESS STEEL CORRUGATED PIPE

| | |
|--|---------------------------------|
| MATERIAL | Material No. 1.4404 (AISI 316L) |
| TEMPERATUREINSATZBEREICH | -270 °C to 600 °C |
| MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C | DN 16: 11 bar DN 20: 11 bar |

INSULATION MADE OF EPDM

| | |
|----------------------|--|
| MATERIAL | Light, flexible, closed-cell, synthetic rubber. Free of PVC and CFC (according to legal requirements). No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304 |
| TEMPERATURE RANGE | +150 °C, short-term up to +175 °C (stagnation temperature of collectors) |
| THERMAL CONDUCTIVITY | 0,036 W/mK at 0 °C 0,038 W/mK at 40 °C |
| FIRE BEHAVIOUR | Euro class E (DIN EN 13501-1) |



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE® | inox rapid pro

| Reference | SAP | Length (m) |
|--------------|---------|------------|
| DN 16 | | |
| 16 x 13/10 m | 3032236 | 10 |
| 16 x 13/25 m | 3032237 | 25 |
| 16 x 13/50 m | 3032238 | 50 |
| 16 x 25/10 m | 3032261 | 10 |
| 16 x 25/25 m | 3032262 | 25 |
| 16 x 25/45 m | 3032263 | 45 |
| DN 20 | | |
| 20 x 13/10 m | 3032244 | 10 |
| 20 x 13/25 m | 3032246 | 25 |
| 20 x 13/50 m | 3032247 | 50 |
| 20 x 25/10 m | 3032264 | 10 |
| 20 x 25/25 m | 0302266 | 25 |
| 20 x 25/45 m | 3032267 | 45 |