



SOLAR-TUBE®

eco combi

SHEATHING

MATERIAL	Polyolefin film
	Very good ozone resistance, UV-resistant

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
TEMPERATURE RANGE	-270 °C to 600 °C
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 200 °C	DN 16: 9,8 bar DN 20: 6,1 bar DN 25: 6,1 bar

SENSOR CABLE

2 x 0,75 mm² VDE 7507

INSULATION MADE OF EPDM

MATERIAL	Light, flexible, closed-cell, synthetic rubber. Free of PVC and CFC (according to legal requirements). No embrittlement of copper and stainless steel pipes (DIN 1988 Part 200) Dimensions and tolerances according to DIN EN 14304
TEMPERATURE RANGE	+150 °C, short-term up to +175 °C
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,038 W/mK at 40 °C
FIRE BEHAVIOUR	Euro class E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

SOLAR-TUBE® | eco combi

Reference	SAP	Length (m)
DN 16		
16 x 13/10 m	3052690	10
16 x 13/15 m	3052691	15
16 x 13/20 m	3052692	20
16 x 13/25 m	3052693	25
DN 20		
20 x 13/10 m	3052694	10
20 x 13/15 m	3052695	15
20 x 13/20 m	3052696	20
20 x 13/25 m	3052697	25