



AEROLINE®

inox terra PE

JACKET PIPE

MATERIAL	Double-walled cable protection pipe with smooth inner wall made of PE-HD
RING STIFFNESS	Ring stiffness according to DIN 16961, SN24 $\geq 16.0 \text{ kN/m}^2$
OUTER DIAMETER	160 mm
MINIMUM BENDING RADIUS	42,5 cm

STAINLESS STEEL CORRUGATED PIPE

MATERIAL	Material No. 1.4404 (AISI 316L)
MAXIMUM PERMISSIBLE OPERATING PRESSURE AT 95 °C	DN 32: 6,5 bar DN 40: 5,8 bar

ELECTRICAL INSTALLATION PIPE 32

INNER DIAMETER	25 mm (DIN EN 50086): for control, sensor or electrical load cables
----------------	---

INSULATION MADE OF EPDM

MATERIAL	Flexible insulation made of foamed, closed-cell polyethylene Dimensions and tolerances in accordance with DIN EN 14303 DN 25/ DN 32: 13 mm DN 40: 9 mm
THERMAL CONDUCTIVITY	0,036 W/mK at 0 °C 0,040 W/mK at 40 °C
FIRE BEHAVIOUR	Euroclass E (DIN EN 13501-1)



NMC sa
Gert-Noël-Strasse · B-4731 Eynatten
Tel.: +32 87 85 85 00 · Fax: +32 87 85 83 55
E-Mail: info@nmc.eu
www.nmc-insulation.com



PRODUCT RANGE

AEROLINE®

inox terra PE

Reference	SAP	Length (m)
DN 32		
DN 32, length 5 m	3032659	5
DN 32, length 7,5 m	3032660	7,5
DN 32, length 10 m	3032661	10
DN 32, length 12 m	3032662	12
DN 32, length 14 m	3032663	14
DN 32, length 17,5 m	3032664	17,5
DN 32, length 20 m	3032665	20
DN 32, length 25 m	3032666	25
DN 40		
DN 40, length 5 m	3032693	5
DN 40, length 7,5 m	3032694	7,5
DN 40, length 10 m	3032695	10
DN 40, length 12 m	3032696	12
DN 40, length 14 m	3032697	14
DN 40, length 17,5 m	3032698	17,5

PRODUCT RANGE
AEROLINE®

inox terra PE

Basic Accessory Set



Description	Reference	SAP	Set/CAR	
2x Rubber end cap 160 1x Connection set 1x Bending aid	DN 25	3059493	1	
	DN 32	3059494	1	
	DN 40	3059495	1	

Premium Accessory Set



Description	Reference	SAP	Set/CAR	
2x Rubber end cap 160 1x Connection set 1x Bending aid 1x Route warning tape 1x Masonry sealing set	DN 25	3059493	1	
	DN 32	3059494	1	
	DN 40	3059495	1	